# Ethernet I/O Modules: ADAM-6000

ADAM-6000 Series	Smart Web Ethernet I/O Modules	5-2				
ADAM-6000 Series	I/O System Architecture & Product Category	5-4				
ADAM-6000 Series	System Configuration & Application Development Tool	5-6				
ADAM-6000 Series Selection Guide	9	5-8				
Communication Controller						
ADAM-6501	Ethernet-based Communication Controller	5-10				
Wireless LAN Input/Output						
ADAM-6050W/6051W/6060W	Wireless LAN-enabled Input/Output Modules	5-12				
Ethernet Networking						
ADAM-6520/6521	5-port Industrial Ethernet Switches with Fiber Optic Switch	5-14				
ADAM-6541	Multi-mode Ethernet to Fiber Optic Converter	5-14				
ADAM-6542	Ethernet to Single Strand WDM Fiber Optic Converter	5-14				
Digital Input/Output, Counter/Relay						
ADAM-6050	12-ch Digital Input/Output Module	5-15				
ADAM-6051	12-ch Digital Input/Output/Counter Mixed Module	5-15				
ADAM-6052	16-ch Source Type Digital Input/Output Module	5-15				
ADAM-6060	6-ch Digital Input/Relay Module	5-16				
ADAM-6066	6-ch Digital Input/Power Relay Module	5-16				
Analog Input/Output						
ADAM-6015	7-ch RTD Input Module	5-16				
ADAM-6017	8-ch Analog Input Module	5-17				
ADAM-6018	8-ch Thermocouple Input Module	5-17				
ADAM-6024	12-ch Universal Input/Output Module	5-17				
ADAM-6022	Dual-loop PID Controller	5-18				
ADAM-6000 Series Dimensions		5-18				

mk K ma

OUTPUT

S. S.

ADAM-6017

0

5

ADAM-6520 Power 00/10M(Port 1) DI10M(Port 2) (10M(Port 3) OM(Port 4) M(Port 5)

Data Acquisition Modules

ort Industrial s Ethernet Swi

Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com

ADAM-6051

on Module

TRO

DAM-6060

# **ADAM-6000** Series



#### Features

- Ethernet-based smart I/O
- Mixed I/O in single module
- Pre-built HTTP server and web page in each module for data/ alarm monitoring
- User-defined web pages
- Active alarm/event trigger handling
- Industrial Modbus/TCP protocol
- Remote F/W upgrade through the internet
- · Pre-built mathematic functions in analog input modules
- ADAM.Net Class Library software support

## The Path to Seamless Integration

The integration of automation and enterprise systems require a change in the architecture of open control systems. From Advantech's point of view, the level of integration between automation and enterprise systems can only be accomplished through Internet technology. The seamless level of integration between plant floor and office floor has not been achieved in all automation systems. However, many enterprises are approaching this goal.

The key element of the seamless integration is a common network architecture, which breaks the traditional layers (enterprise layer, plant information layer, control layer and device level layer, sensor layer) that require a data gateway as an interface to communicate between different layers. Industrial Ethernet is regarded as the most appropriate network to accomplish the task in industrial automation.

It is believed that IP/Ethernet protocols will progress beyond the control layer, into the field layers. Placing remote I/O with IP/Ethernet connections on the shop floor is economical. Advantech believes that over the next five years, Internet protocols over Ethernet will dominate major field connections. The Advantech ADAM-6000 series comprises industrial-grade Ethernet hubs/switches/fiber optics for infrastructure Ethernet solutions in industrial automation environments.

#### Control Strategy Moves to Field Devices

It is a trend to move I/O to remote locations to reduce wiring costs. Remote I/O is becoming smarter and equipped with control functions as they move from today's 16 to 64 I/O multi-plexers to the smallest remote I/O units, with perhaps as few as four I/O in the near future.

The ADAM-6000 series is designed to realize the concept of the smart I/O blocks. With control algorithms and mathematical functions built in, the ADAM-6000 series is a revolutionary smart I/O module close to the sensor layer in automation.



The Future Concept of Smart I/O Blocks

#### Web-enabled Technology Becomes Popular on Factory Floors

As Internet technologies and standards have rapidly developed over the past decade, Web-based control methodologies now obviously represent a powerful opportunity for extending efficient network-based management techniques to encompass non-IT real-world assets.

The ADAM-6000 series is equipped with a built-in web server so that its data can be viewed, anytime-anywhere via the Internet. Moreover, ADAM-6000 allows users to configure user-defined web pages to meet the diverse needs in various applications. With this powerful function, the ADAM-6000 series breaks the boundary of traditional multi-layer automation architecture and allows users to access field data directly in real time, which enables seamless integration between the plant floor and the front office.

HMI has provided a friendly operator interface for discrete control and sharply reduced the cost and complexity of automation systems. A web server has been added to most HMI software and a browser allows access to HMI displays from remote locations via the network. The end user is able to see and use an identical HMI from any Internet connected computer anytime, anywhere. ADAM-6000 can be be fully integrated with standard HMI software which supports Modbus TCP/IP, including Advantech Studio.



**ADAM-6000 Application Architecture** 

## ADAM-6000 Smart Web Ethernet I/0

The integration of automation and enterprise systems and the adoption of an emanufacturing strategy requires a shift in the manufacturing system architecture. E-manufacturing demands open access to real-time production data from the field. To achieve a seamless level of integration between plant floors and the enterprise level, some fundamental changes have to occur in I/O systems. E-manufacturing means the power of the Internet and I/O systems are used to take things one step further by leveraging Internet technology. These revolutionary I/O systems are web-enabled, smart and are "just-fit" mixed I/O modules. Improvement of the PLC has been gradually moving from logic and I/O in a single chassis, to I/Os in remote locations. The ADAM-6000 series is based on the concept described above.

## Why Smart I/O ?

To meet the requirements of future automation, smart I/O blocks have become popular in I/O system design. To implement the smart I/O blocks concept, I/O systems should be placed as close to the field sensors as possible. Therefore, intelligent control algorithms or basic mathematical functions are essential in I/O systems. ADAM-6000 provides intelligent functions that accelerate future automation development.

## Why Web I/O ?

The Internet is the major technology that allows all levels of an organization to be able to communicate and make the sensor-to-boardroom model a reality. Access can be realized from any device that utilizes a standard web browser, so connections between remote manufacturing plants, production planners, plant managers, and the CEO can be made without having to create a dedicated proprietary network. Since a web page can be installed in the I/O system as a Web I/O, then not only a sensor-to-boardroom model can be practiced, but sensor-to-home, and a sensor-to-mobile display can also be realized. ADAM-6000 Smart Web Ethernet I/O modules provide built-in standard and customizable web pages, which truly demonstrate the power of Web I/O.

## Why Mixed I/O ?

The impact of a tailor-made business model is spreading in automation, and I/O design is no exception. Over the past few years, the average size of PLCs have been reduced by the use of many small and micro PLCs to replace larger PLCs. A compact-sized and application-oriented mixed I/O is the trend. A just-fit mixed I/O module reduces the engineering effort, as well as installation and maintenance cost. It simplifies system architecture and increases system reliability. Obviously the ADAM-6000 series is the perfect choice to meet the specific requirements of many vertical markets.

## **Common Key Features**

#### **1.Industrial Ethernet Networking**

The ADAM-6000 series provides various communication modules such as Ethernet hubs, Ethernet switches and Ethernet switches with fiber ports. ADAM-6000 supports both Modbus/TCP and UDP. Embedded with a 10/100 Mbps Ethernet chip, ADAM-6000 supports industrial Modbus/TCP over TCP/IP networks which are commonly used in most business environments. ADAM-6000 also supports UDP, which allows users to develop their applications and handle events.

#### 2.Smart and Mixed I/O Modules

ADAM-6000 provides built-in mathematical functions, including MAX, MIN, AVG, and others in analog input/output modules. ADAM-6000's mixed I/O modular design optimizes the performance and usage of I/O and minimizes the engineering efforts and maintenance cost.

#### 3.Built-in Standard and User-defined Web Pages

ADAM-6000 adopts web technology to enable remote monitoring via Internet. In addition to standard web pages, ADAM-6000 allows users to use the Java programming language to develop pages to meet their own requirements. ADAM-6000 supports standard HMI software with Modbus/TCP OPC drivers and ActiveX drivers.



ADAM-6000 Application Diagram



### **I/O System Architecture**



The ADAM-6000 is a controller independent, distributed I/O solution with modular design for maximum flexibility. Its powerful onboard intelligence makes it well suited to SCADA and stand-alone control applications.

## **Ethernet-enabled Networking**

The ADAM-6000 series Ethernet-enabled data acquisition and control module works as an Ethernet I/O data processing center. This new product is not only a standard I/O, but also an intelligent system designed with local control functions and a Modbus/TCP standard for users to easily develop various applications over Ethernet.

## **Analog Input Modules**

The ADAM-6000 analog input modules use microprocessor-controlled, high-resolution, 16-bit, sigma-delta A/D converters to acquire sensor signals such as voltage, current, thermocouple or RTD. They translate analog data into two's complement. After the modules receive a request from the host, they send the data in the desired format over the Ethernet network. ADAM-6000 analog input modules protect your equipment from ground loops by providing 3000 V<sub>DC</sub> isolation. The ADAM-6017 and ADAM-6018 modules feature digital outputs which may also be used for alarms and event counting. The analog input module's two digital output channels are open-collector transistor switches that you can control from the host computer. By switching solid state relays, the output channels can control heaters, pumps and other power equipment. The module can use its digital input channel to sense the state of a remote digital signal.

## **Programmable Alarm Output**

Analog input modules include high and low alarm signals with remotely configurable boundary values. After each A/D conversion, the digital value is compared with the high and low limit. The module can change the state of a digital output depending on the result of this comparison. This function allows it to perform on/off control of a device independently of the host PC.

#### Independent Channel Input Type Configuration

The ADAM-6015 6-channel RTD module, provides independent channel input type configuration. You can configure PT-100, Pt-1000 or Balco mA for each channel. This independent channel input type configuration gives the ADAM-6015 more flexibility for versatile applications. This functionality saves customers the cost of buying multiple modules and reduces inventory as well.

## I/O System Architecture

#### **Loop Controller Module**

The ADAM-6022 offers two analog inputs, two analog outputs, two digital inputs and four digital outputs in one module. The ADAM-6022 is a two loop PID controller. Each loop may be configured as single loop, dual loop ratio, dual loop cascade or single loop with override. An auto tune function is provided to maximize the effectiveness of the control.

#### **Analog Input Modules**

The ADAM-6017/6018 are 16-bit, 8-channel analog input modules that provide programmable input ranges on all channels. These modules are an extremely cost-effective solution for industrial measurement and monitoring applications.  $3000 V_{DC}$  optical isolation between the analog input and the modules protects the modules and peripherals from damage due to high input-line voltages.

The ADAM-6018 also supports thermocouple input in combination with the ADAM-6015 7 channels RTD input module. These two modules can offer a complete solution for temperature measurement applications.

#### **Digital Input and Output Modules**

The ADAM-6050 features twelve isolated digital input channels and six isolated digital output channels. The outputs are open-collector transistor switches that you can control from the host computer. You can also use the switches to control solid-state relays, which in turn can control heaters, pumps or other power equipment. The host computer can use the module's digital inputs to determine the state of limit switches, safety switches or remote digital signals. The ADAM-6051 provides twelve isolated digital input channels, two isolated digital output channels and two counter channels. All have 5000  $V_{\text{RMS}}$  isolation to prevent ground loop effects and prevent damage from power surges on the input lines.

#### **Digital Input**

The ADAM-6050 & ADAM-6051 digital input channels provide four operational modes:

- Normal digital input with inverter setting
- 3 kHz frequency
- 3 kHz counter with digital filter
- Hi-to-Lo, Lo-to-Hi latch

Each digital input channel can set its operational mode independently.

#### **Digital Output**

The ADAM-6050 & ADAM-6051 digital output channels also provide four operational modes: normal digital output, pulse output with continuous or burst count mode, Hi-to-Lo, Lo-to-Hi delay. Each digital output channel can set its operational mode independently as well.

#### **Counter/Frequency**

The ADAM-6051 offers two 32-bit counter channels and a built-in programmable timer for frequency measurement.

#### **Programmable Alarm Output**

The ADAM-6051 modules include two digital output channels for alarm functions. You can set alarm values (32-bit) into the module from your host computer.

#### **Relay Output Module**

The ADAM-6060 offers six isolated digital input channels and six isolated relay channels. The digital input channel accepts 10 ~ 30 V<sub>DC</sub> input. Just like other ADAM modules, the ADAM-6060 relay module is controlled remotely and stores its configuration data in EEPROM. It provides six Form A relay channels with 24 V<sub>AC</sub> output. This module is excellent for on/off control or low-power switching applications.

#### 12-ch Universal Input/Output Module

The ADAM-6024 offers six analog inputs, two analog outputs, two digital inputs and two digital outputs. This module is especially cost-effective for applications that require various signal type I/O points. The ADAM-6000 series also offers analog output functions.

## **System Configuration & Application Development Tools**

## **Software Support**

Based on the Modbus/TCP standard, the ADAM-6000 firmware has a built-in Modbus/TCP server. Advantech provides the necessary DLL drivers, OPC Server, and ADAM.Net Utility for the ADAM-6000. You can configure this DA&C system via ADAM.Net Utility and integrate it with a HMI software package via Modbus/TCP driver or Modbus/TCP OPC Server. Furthermore, you can use the DLL driver to develop your own applications.

## **ADAM.Net Utility**

For system configuration, ADAM.Net Utility offers a friendly operating environment to calibrate I/O modules, monitor current data, set IP addresses etc. As you execute this program, it will automatically search each ADAM-6000 device on the network. There are also some advanced functions, such as the scaling function, which helps users convert various field signals to engineering units, and a latch output function, which forces data or status to create system simulations.

## **Browser-based Online Monitoring**

Each ADAM-6000 module features an embedded HTTP server for remote monitoring and diagnostics. The ADAM-6000 also pre-builds a default html page in each module for online support for monitoring analog input/output, digital input/output, alarm/event, counter, or real-time values, all done remotely via the Intranet/Internet. Just enter the IP address of the ADAM-6000 module in any standard browser, and you can get dynamic, real-time values of ADAM-6000 I/O modules immediately, without any required programming.

File Tools Setup Help	(FormTCPIF)				
Ton See Hay     Ton See	Hortname: Adapter Consection timeout Genetising the set.	Minochen-nb [72:18:3:32 [800	m	Apply	
tis mody!					
eAutomation Utility Venion 1 00.04			_		
	EBenetiO	Ministry, 1922         465/4972         2 and           PD 100 C5 -44 92         7 72 10 3 300           PT 21 10 3 300         7 75 255 254 0           PT 20 3 300         7 50 300           PT 10 3 300         7 50 300	adEreat   Parovoat   Fa	Apply change	
RefinshMetwork:	×				<u> </u>
eAutomation Utility Version 1.00.04 - (Form File Tools Setup Help	uMam60XXDIO]				
Supersonal State S	P Element I/O)  P Element I/O)  Channel to C	0 19-th wolded Agaba (JO and mage (Molow)	Description           D10           D10           D112           D14           D15           D10           D110           D111           D00           D03           D04           D05	Mote Construct C	=

#### How to Develop Applications



## System Configuration & Application Development Tools

### **ActiveX Controls**

Advantech offers an easy-to-use integration tool, Modbus/TCP ActiveX Controls for ADAM-6000 I/O data access. This can be used for users to develop applications with VB, VC, and other Windows development kits. (Note: The UDP function isn't fully supported in the existing version.)

### **DLL Driver**

Advantech also offers another easy-to-use integration tool, the ADAM-6000 DLL driver, for users to develop their own applications with VB, VC, BCB, Delphi, and other Windows development kits.

## **Customizeable Web Page**

Since the ADAM-6000 modules have an embedded web server with one default web page. users can monitor and control the I/O status everywhere. The ADAM-6000 modules data can also be downloaded to one user-defined web page for custom applications. These contigurations can be downloaded into ADAM-6000 modules via ADAM.Net Utility.

To create a web page for ADAM-6000 modules is quick and easy. The following steps show a simple method to configure your own web page in short time.

## **ADAM.NET Class Library**

Advantech has created the VB.Net and C# library for ADAM-4000, 5000/485, 5000/TCP, 6000 series I/O, It offers a powerful tools for Microsoft Virtual Studio.Net 2003/2005 that allows users to easily implement the ADAM series I/O into theirapplications under Windows Embedded XP and WinCE.Net platform.





AD\ANTECH

## **ADAM-6000 Selection Guide**

Module Spec.		ADAM- 6015	ADAM-6017	ADAM-6018	ADAM-6022	ADAM- 6024	ADAM-6050	ADAM-6051	ADAM- 6052	ADAM- 6060	ADAM-6066	ADAM- 6050W	ADAM- 6051W	ADAM- 6060W
Interface*					L	10/100 Mt	ops Ethernet		1			802.1	1 b wireless	LAN
	Resolution	16 bit	16 bit	16 bit	16 bit for Al 12 bit for AO	16 bit for Al 12 bit for AO	-	-	-	-	-	-	-	-
	Input Channels	7 differential	8 differential	8 differential	6 differential	6 diff. Al	-	-	-	-	-	-	-	-
	Sampling Rate			10 samples/se	c		-	-	-	-	-	-	-	-
ut	Voltage Input	PT-50 PT-100 PT-200 PT-1000 Balco 500 NI 50	±150 mV ±500 mV ±1 V ±5 V ±10 V	-	±10 V	±10 V	-	-	-	-	-	-	-	-
alog Inp	Current Input		0 ~ 20 mA 4 ~ 20 mA	0 ~ 20 mA 4 ~ 20 mA	0 ~ 20 mA 4 ~ 20 mA	0 ~ 20 mA 4 ~ 20 mA	-	-	-	-	-	-	-	-
Ar	Direct Sensor Input	Pt, Balco and Ni RTD	-	J.K.T.E.R.S.B. Thermocouple	-	-	-	-	-	-	-	-	-	-
	Burn-out Detection	Yes	-	Yes	-	-	-	-	-	-	-	-	-	-
	Channel Independent Configuration	Yes	Yes	Yes	Yes	Yes	-	-	-	-	_	-	-	-
	Math. Functions	Max. Min. Avg.	Max. Min. Avg.	Max. Min. Avg.	-	-	-	-	-	-	-	-	-	-
t	Output Channels	-	-	-	2 A0	2 A0	-	-	-	-	-	-	-	-
nalog Outpu	Voltage Output	-	-	-	0 ~ 20 mA, 4 ~ 20 mA with 15 V <sub>DC</sub>	0 ~ 20 mA, 4 ~ 20 mA with 15 V <sub>DC</sub>	-	-	-	-	-	-	-	-
1	Drive Current	-	-	-	$0 \sim 10 V_{DC}$ with 30 mA	0 ~ 10 V <sub>DC</sub> with 30 mA	-	-	-	-	-	-	-	-
+	Digital Input Channels	-	-	-	2	2	12	12	8	6	6	12	12	6
and Outpu	Digital Output Channels	-	2 (Sink)	8 (Sink)	2 (Sink)	2 (Sink)	6 (Sink)	2 (Sink)	8 (Source)	6-channel relay	6-channel power relay	6 (Sink)	2 (Sink)	6-channel relay
ital Inpul	Event Counter	-	-	-	-	-	-	2 (4.5 kHz)	-	-	-	-	2 (4.5 kHz)	-
Dig	High/Low Alarm Settings	Yes	Yes	Yes	-	-	-	-	-	-	-	-	-	-
	Isolation						2,	000 Vrms						
Wa	tchdog Timer							Yes						
	Remark	-	-	-	Built-in Dual Loop PID Control Algorithm	-	-	-	-	-	-	-	-	-
	Page	5-16	5-	-17	5-18	5-17		5-15		5	-16		5-12	

5-8 AD\ANTECH Courtesy of Steven Engineering, Inc.

Name	ADAM-6501	ADAM-6520/6521	ADAM-6541/6542		
Interface	10/100Base-T	10/100Base-T, 100Base-FX	10/100Base-TX and 100Base-FX		
Ethernet Port	1	5	2		
Serial Port	2	-	-		
Speed	10/100 Mbps	up to 100 Mbps	up to 100 Mbps		
Parity	Even, odd, none, space, mark	-	-		
Data Bit	5, 6, 7, 8	-	-		
Stop Bit	1, 1.5, 2	-	-		
Software	Configuration/ port mapping utility	-	-		
Connector	Network: RJ-45 Serial: RJ-48 & Screw Terminator	Network: RJ-45 Fiber: SC type multi/single mode	Network: RJ-45 Fiber: SC type multi-mode ST type single-mode		
Mounting	DIN 35 rail, stack, wall				
Power Requirement	10 - 30 V				
Power Consumption	4 W	6520: 2.4 W 6521: 3 W	3 W		
Operating Temperature	0 ~ 55° C	-10 ~ 65° C	-10 ~ 65° C		
Page	5-10	5-14			

## **Selection Guide**



# ADAM-6501

## Web-enabled Universal Communication **Controller with Intel® XScale**



#### **Features**

- · Powerful Ethernet-enabled communication controller in a tiny package
- Built-in Windows CE .NET to run embedded Ethernet applications
- Embedded web server
- Microsoft embedded VC++ development environment supported
- Built-in CompactFlash<sup>®</sup> slot
- Built-in Flash disk for Win CE and user applications
- Built-in 32 MB real-time clock and watchdog timer
- Offers RS-232 and RS-485 series communication port
- Automatic data flow control in RS-485 mode
- Communication speed up to 115.2 kbps
- Easy to mount on a DIN-rail or wall
- ADAM.Net Class Library software support

## Introduction

ADAM-6501 is a fully functional Ethernet-enabled controller for industrial automation and control. It provides an ideal environment to develop applications converting RS-232/485 devices/equipment data to the Ethernet/Internet world with minimum effort. Their built-in Windows CE .NET operating system lets users run new programs produced in Microsoft embedded VC++ & VS.Net development Software. The Windows environment also includes a web server to allow the designer to develop web-enabled applications.

## **Specifications**

#### General

- Connectors
- Enclosure
- LED Indicators
- Mounting
- Power Consumption
- Power Input
- Real-time Clock
- Watchdog Timer

#### **System Hardware**

- CPU
- 32-bit Intel® XScale 400 MHz 32 MB flash memory

CE. FCC claas A

DIN 35 rail, stack, wall

Yes, programmable

ABS+PC

Yes

4 W @ 24 V<sub>DC</sub>

- Flash Memory RAM
- 64 MB SDRAM Battery Backup RAM 2 MB
  - - 1 x CompactFlash slot (external)

#### Protection

Storage

Power Reversal Protection

#### Software

- Operating System
- System Management
- Windows® CE .NET Web-based remote configuration via standard browser with Java® support.

1 x RJ-45 (LAN), 1 x RJ-48 (RS-232), Plug-in screw

terminal blocks (RS-485 and power)

Power, diagnostics, communications

Unregulated 10 ~ 30 V<sub>DC</sub> (max. 6 W)

Command line configuration in console mode.

#### **Communications**

- Default Setting
  - Onboard
- Recovery LAN
- Serial Ports (Isolated)
- 1 x 10/100Base-T (RJ-45) 1 x RS-232 (RJ-48), 1 x RS-485 Speed: 115.2 kbps
- Protocols Supported TCP/IP. UDP

#### Environment

- Humidity 5~95% RH, non-condensing
- **Operating Temperature** 0 ~ 55° C
- Storage Temperature -20 ~ 80° C (-13 ~ 185° F)

### **Ordering Information**

- ADAM-6501
- Web-enabled Universal Communication Controller



ADAM-6501 Modules Installed as Controllers in a Typical System

5-10 AD\+NTECH Ethernet I/O Modules Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com

## **Feature Details**

#### **Built-in Ethernet and RS-232/485 COM Ports**

The ADAM-6501 has one Ethernet (10/100BASE-T), one RS-232 and one RS-232/485 ports. These provide easy communication between the controller and devices in your applications, and has been designed for program downloading, debugging and linking serial devices with the Ethernet/Internet. ADAM-6501 is equipped with a COM1 port (RS-232) supporting full RS-232 signals for applications such as modem connections, while the 3-pin RS-232 and RS-485 are designed as the interface for traditional RS-232/485 devices/equipment. This design allows the controller to be used in a variety of applications. For example, the user may download a data logging application into the ADAM-6501's memory while the ADAM-6501 is connected to a RS-485 network, and then collect the data over the network.

#### **Built-in Real-time Clock and Watchdog Timer**

The real-time clock in the controller ensures accurate time recording when the system operates. The watchdog timer is designed to automatically reset the CPU if the system fails.

#### ADAM-6501AS PC-Based HMI Station/SCADA

The ADAM-6501AS embeds Advantech Studio into ADAM-6501 hardware. So you can easily develop the required application in a desktop PC, then download it into ADAM-6501AS as a cost effective, compact size SCADA/HMI station. Advantech Studio (AStudio), a powerful, integrated collection of automation tools that includes all the building blocks required to develop modern Human Machine Interfaces (HMI), and Supervisory Control and Data Acquisition System (SCADA) applications. AStudio in ADAM-6501AS can run native on Windows CE.NET or in an Internet and Intranet environment. A simple drag and drop, point and click development environment mimics the most complex behavior of your live processes. AStudio is an eAutomation solution that allows designers to develop web-enabled applications.

#### **Applications**

- Distributed data acquisition and control
- Embedded control application (Advantech AStudio SCADA Software)
- Data logging applications
- Serial to Ethernet conversion
- · Web-enabled data acquisition and control



#### **ADAM-6501**

ADAM-6501

6

Existing Control System

Fieldbus

00



## **ADAM-6050W ADAM-6051W ADAM-6060W**

**18-ch Wireless LAN-enabled DI/O Module** 16-ch Wireless LAN-enabled Isolated I/O w/Counter Module

6-ch Wireless LAN-enabled Relay Output Module



#### **Features**

- Supports IEEE802.11b wireless LAN
- Embedded web server with built-in web page
- Supports Modbus/TCP & UDP protocols •
- Supports event trigger function

## Introduction

ADAM-6050W, ADAM-6051W, and ADAM-6060W bring wireless LAN communication to your network. The hardware design of the modules were based on ADAM-6050, 6051, and 6060, but a wireless LAN interface has replaced the RJ-45 Ethernet port. With support for the common IEEE802.11b, these modules can be accessed on your wireless LAN without any hardwiring. A sensible choice for environments with wiring limitations, or expensive wiring requirements.

## **Specifications**

#### General

		··· · · · · · · · · · · · · · · · · ·	, , , , , , , , , , , , , , , , , , ,
<ul> <li>Certifications</li> </ul>	CE, FCC class A		Breakdown voltage: 500 V <sub>AC</sub> (50/60 Hz)
<ul> <li>Connectors</li> </ul>	Plug-in screw terminal block (#14 ~ 28 AWG)		Relay on time: 7 msec; Relay on time: 3 ms
<ul> <li>Dimensions (WxHxD)</li> </ul>	70 x 112 x 25 mm		Insulation resistance: 1 GO minimum at 500 Vac
<ul> <li>Enclosure</li> </ul>	ABS+PC		
- LAN	IEEE802.11b WLAN	Protection	
LED Indicators	Power, communication, signal, strength	Isolation Voltage	2.000 V <sub>PMS</sub>
<ul> <li>Mounting</li> </ul>	DIN 35 rail, stack, wall	<ul> <li>Power Reversal Protect</li> </ul>	tion
<ul> <li>Power Consumption</li> </ul>	ADAM-6050W. ADAM-6060W: 2 W @ 24 Vdc		
· · · · · · · · · · · · · · · · · · ·	ADAM-6051W: 2.5 W @ 24 Vdc	Software	
<ul> <li>Power Input</li> </ul>	Unregulated 10 $\sim$ 30 V <sub>pc</sub>	<ul> <li>Support Protocol</li> </ul>	Modbus/TCP and UDP
<ul> <li>Watchdog Timer</li> </ul>	Yes, programmable	<ul> <li>Web Server</li> </ul>	Embedded, with web page for configuration
Communications		Environment	
<ul> <li>Channels</li> </ul>	ADAM-6050W: 12 DI. 6 DO	<ul> <li>Humidity</li> </ul>	5 ~ 95 % RH. non-condensing
	ADAM-6051W: 12 DI/2 DO/2 Counter	<ul> <li>Operating Temperature</li> </ul>	-10 ~ 60 °C (14 ~ 140 °F)
	ADAM-6060W: 6 DI, 6 Relay	<ul> <li>Storage Temperature</li> </ul>	-25 ~ 85 °C (-13 ~ 185 °F)
<ul> <li>Counter</li> </ul>	Maximum Count: 4,294,967,285 (32 bit)	otorago romporataro	
	Input frequency: 0.3 ~ 4500 Hz max. (frequency mode)	Ordoning Info	rmation
	4500 Hz max. (counter mode)	Videring mit	manon
	Modes: Counter, Frequency	ADAM-6050W	18-ch Wireless LAN-enabled DI/O Module
<ul> <li>Digital Input</li> </ul>		ADAM-6051W	16-ch Wireless LAN-enabled Isolated I/O w/Coun
Dry Contact:	Logic level 0: Close to GND		Module
Wet Contest	Logic level 1: Upen (Status Inversable by utility)	ADAM-6060W	6-ch Wireless LAN-enabled Relay Output Module
wei Contact	(ADAM-0000W AILU ADAM-0001W UILIY)		
	Logic level 1: $\pm$ 10 to 30 V		
Counter Mode	Up to 3 kHz for ADAM-6050W/6060W		
	Up to 4.5 kHz for ADAM-6051W		
Frequency Mode:	Up to 3 kHz for ADAM-6050W/6060W		
	Up to 4.5 kHz for ADAM-6051W		
<ul> <li>Digital Output</li> </ul>	Open collector to 30 V, 100 mA max. load 300 mW		
	Pulse output : up to 5 kHz for ADAM-6050W and		
	ADAM-6051W		

• Relav Output (Form A) Contact rating: AC: 120 V @ 0.5 A. DC: 30 V @ 1 A 50/60 Hz) ff time: 3 ms nimum at 500 V<sub>DC</sub>

**ADAM-6050W ADAM-6051W ADAM-6060W** 

## **Feature Details**

• Embedded web page Event trigger function

Data stream function

Modbus/TCP supported

#### Communication

ADAM-6050W, ADAM-6051W and ADAM-6060W support IEEE802.11b, so they can connect to most wireless LAN access points.

Like other ADAM-6000 modules, ADAM-6050W, ADAM-6051W and ADAM-6060W also support the Modbus/TCP and UDP protocols. You can use HMI/SCADA software to communicate with the modules through Modbus/TCP. The pre-built UDP protocol supports event trigger and data streaming functions for critical and real time responses.

#### **Embedded Web Server with Built-in Web Page**

The modules have an embedded web server with a built-in webpage that can be configured by an utility for: Tag Name, Status Label (for example, Start/Stop, Run/Stop, Enable/Disable and Alarm/Normal), and Channel Enable.

Although it is based on Java technology, there is no need to learn how to write Java applets to design a customized web page. By using ADAM-6000 utility software, the webpage can be customized to exact requirements.

> DAM (R)

IEEE802.11b

 Easy to install with no extra wiring Compatible with standard Wireless LAN

compatible Wireless LAN

## **Home/Building Applications**



## **Port Crane Monitoring & Control Applications**





Online Download www.advantech.com/products AD\ANTECH 5-13 Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com



## ADAM-6520 ADAM-6521 ADAM-6541 ADAM-6542

5-port Industrial 10/100 Mbps Ethernet Switch 5-port Industrial 10/100 Mbps Ethernet Switch with Fiber Optic Ethernet to Multi-mode Fiber Optic Converter Ethernet to Single Strand WDM Fiber Optic Converter



- **Specifications**  Standard IEEE 802.3, IEEE 802.3u LAN ADAM-6520 : 10/100Base-T standard network ADAM-6521 : 10/100Base-T & 10/100 Base-FX standard • Transmission Distance Ethernet: 100 m, Multi-mode Fiber: Up to 2 km (ADAM-6521) Transmission Speed ADAM-6520 : up to 10/100 Mbps ADAM-6521 : 4 x 10/100 Mbps & 1 x 100 Mbps (Fiber) ADAM-6520 : RJ-45, Connectors ADAM-6521 : 4 x RJ-45 & 1 x Fiber (SC type) LED Indicators Power, 10/100 Mbps Power Inputs Unregulated 10 ~ 30 V<sub>DC</sub> Power Consumption 2.4 W @ 24 V<sub>DC</sub> ABS with captive mounting hardware Enclosure Operating Temperature -10 ~ 65° C (14 ~ 149° F) Storage Temperature -20 ~ 80° C (14 ~ 176° F) Operating Humidity 20 ~ 95% (non-condensing)
- Storage Humidity 0 ~ 95% (non-condensing)

## **Ordering Information**

- ADAM-6520
- ADAM-6521

5-port Industrial 10/100 Mbps Ethernet Switch 5-port Industrial 10/100Mbps Ethernet Switch with Fiber port



## **Specifications**

	-		
•	Standard	IEEE 802.3, 802.3u	, 802.3x
•	LAN	10/100Base-TX, 10	10Base-FX
•	Transmission Distance	Ethernet :	100 m
		Fiber:	
		ADAM-6541:	Multi-mode: Up to 2 km,
			Single-mode: Up to 20 km
		ADAM-6542:	Up to 20 km
•	Transmission Speed	Up to 100 Mbps	
•	Connectors	1 x RJ-45	
		1 x SC type fiber op	otic connector (ADAM-6541,
		ADAM-6542/W13,	ADAM-6542/W15)
		1 x ST type fiber op	tic connector (ADAM-6541/ST)
•	LED Indicators	Power, Full/Link (1	00Base-FX),100/10 M Ethernet
		(ADAM-6541)	
		Power, Link (100Ba	se-FX), 100/10 M Ethernet
		(ADAM-6542)	
•	Power Input	Unregulated 10 ~ 3	BO V <sub>DC</sub>
•	Power Consumption	3 W @ 24 V <sub>DC</sub>	
•	Isolation Protection	1,500 V <sub>RMS</sub> (Etherne	et port)
•	Enclosure	IP30, ABS+PC with	solid mounting hardware Mounting
		DIN 35 rail, stack, v	vall Protection
•	<b>Operating Temperature</b>	-10~65°C(14~1	149° F),
		stack : -10 ~ 60° C	(14 ~ 140° F)
•	Storage Temperature	-20 ~ 80° C (-4 ~ 1	76° F)
•	Operating Humidity	20~95% (non-cor	ndensing)
•	Storage Humidity	0~95% (non-cond	densing)

## **Ordering Information**

- ADAM-6541 10/100 Base-TX Ethernet to 100 Base-FX Multi-mode SC Type Fiber Optic Converter
- ADAM-6541/ST 10/100 Base-TX Ethernet to 100 Base-FX Multi-mode
   ST Type Fiber Optic Converter
- ADAM-6542/W15
   10/100Base-TX Ethernet to 100Base-FX WDM Single
   Strand Fiber Optic Converter (Tx:1550nm, Rx:1310nm)
   10/100Base-TX Ethernet to 100Base-FX WDM Single
- ADAM-6542/W13 10/100Base-TX Ethernet to 100Base-FX WDM Single Strand Fiber Optic Converter (Tx:1310 nm, Rx:1550nm)

## ADAM-6050 **ADAM-6051 ADAM-6052**

**18-ch Isolated Digital I/O Module** 

16-ch Isolated Digital I/O w/Counter Module

## 16-ch Source Type Digital I/O Module



ADAM-6050

## **Specifications**

#### General

- Power Consumption
- Watchdog Timer
- **Digital Input**

#### Channels

- Dry Contact
- Wet Contact

#### **Digital Output**

- Channels
- 6 Open Collector to 30 V, 100 mA max. load
- Power Dissipation
  - 300 mW for each module

## **Ordering Information**

**Common Specifications** 

ADAM-6050

## 18-ch Isloated Digital I/O Module

CE FCC

2 W @ 24 V<sub>DC</sub>

(comm.)

12

GND

 $30 V_{DC}$ 

Yes, programmable

Logic level 0: close to



2 W @ 24 V<sub>DC</sub>

(comm.)

2

12

Yes, programmable

4,294,967,285(32 bit)

0.3 ~ 4500 Hz max.

## **Specifications**

#### General

- **Power Consumption**
- Watchdog Timer

#### Counter

- Channels .
- Maximum Count Input Frequency

#### **Digital Input**

#### **Digital Output**

- Channels
- Open Collector to 30 V, 100 mA max. load **Power Dissipation** 
  - 300 mW for each module

## **Ordering Information**

ADAM-6051

**Digital Input** 

16-ch Isolated Digital I/O with Counter Module

#### Protection

- Power Reversal Protection
- Power Reversal Protection
- Isolation Voltage 2,000 V<sub>DC</sub>

#### Environment

- Humidity (Operating)
- Humidity (Storage)
- 0~95% RH (non-condensing)

20~95% RH

(non-condensing)

- Operating Temperature Storage Temperature
- -10 ~ 70° C
  - -20 ~ 80° C

**Specifications** 2 W @ 24 V<sub>DC</sub> Yes, programmable (comm.) 8 Logic level 0: close to GND Logic level 1: open Logic level 0 : +3 V max Logic level 1 : +10 V to

 $30 V_{DC}$ 

#### **Digital Output**

ADAM-6052

Power Consumption

Watchdog Timer

**Digital Input** 

Dry Contact

Channels

General

- Channels
- Vdc - Current

**Ordering Information** 

- ADAM-6052

16-ch Source Type Digital I/O Module



PAC & Software

Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258

ECH 5-15 AD\ANTECH

- Logic level 1: open Logic level 0: 3 V max Logic level 1: 10 ~ Modes

  - Channels

  - Dry Contact
  - Wet Contact

**Online Download** www.advantech.com/products

1 x RJ-45 (LAN) Plug-in screw terminal block (I/O, and power)

10/100Base-T

Power and communication

Unregulated 10 ~ 30 V<sub>DC</sub>

LAN

General

LED Indicators

Certifications

Connectors

**Power Input** 

Support Invert DI Status CE, FCC class A **Digital Output** 

- Support 1kHz Pulse Output

Support 3kHz Counter Input

Support 3kHz Frequency Input

Support High-to-Low Delay Output

#### Support Low-to-High Delay Output

Logic level 1: open Logic level 0 : +3 V max Logic level 1 : +10 V to  $30 V_{DC}$ 

(frequency mode) 4500 Hz max. (counter Wet Contact mode) Counter, Frequency Logic level 0: close to GND

35 V (Source Type) 1 A

# 8

## **ADAM-6060 ADAM-6066 ADAM-6015**

6-ch Digital Input/Relay Module

6-ch Digital Input/Power Relay Module

## 7-ch RTD Input Module



2 W @ 24 Vdc

(Comm.)

6 DI

GND

 $30 V_{DC}$ 

6 Relay

7 ms

3 ms

10 ms

Protection

Module

30 V @ 1 A

Yes, programmable

Logic level 0: close to

Logic level 1: open

Logic level 1: 10 ~

AC: 120 V @ 0.5 A

500 V<sub>AC</sub> (50/60 Hz)

1 G. min. at 500 V<sub>DC</sub>

6-ch Digital Input/Relay

CE, FCC class A

1 x RJ-45 (LAN)

10/100Base-T

Plug-in screw terminal

block (I/O, and power)

Power and communication

Unregulated 10 ~ 30 V<sub>DC</sub>

Ethernet I/O Modules

Logic level 0: +3 V max

ADAM-6060

## **Specifications**

#### General

- Power Consumption
- Watchdog Timer

#### **Digital Input**

- Channels
- Dry Contact
- Wet Contact

#### **Relay Output (Form A)**

- Channels
- Contact Rating
- DC
- Breakdown Voltage
- **Relay On Time**
- Relay Off Time
- Total Switching Time
- Insulation Resistance

## **Ordering Information**

ADAM-6060

## **Common Specifications**

#### General

- Certifications Connectors
- I AN
- **LED Indicators**
- Power Input

#### **Digital Input**

- Support 3 kHz Counter Input
- Support 3 kHz Frequency Input
- Support Invert DI Status



## **Specifications**

#### General

- Power Consumption
- Watchdog Timer

#### **Digital Input**

- Channels
- Dry Contact

Wet Contact

#### **Relay Output (Form A)**

- Channels
- Contact Rating
- DC
- Breakdown Voltage
- **Relay On Time**
- **Relay Off Time**
- **Total Switching Time** 
  - Insulation Resistance

## **Ordering Information**

5-16 ADVANTECH Ethernet I/O Modules Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com

- ADAM-6066
  - Relay Module
- **Digital Output**
- Support Pulse Output •
- Support High-to-Low Delay Output Support Low-to-High Delay Output
- Protection Power Reversal
- . Isolation Voltage

#### Environment

- Humidity (Operating)
- Humidity (Storage)
- **Operating Temperature** .
- Storage Temperature

ADAM-6015	

## **Specifications**

#### eneral

- Power Consumption
- Watchdog Timer
- 2 W @ 24 Vdc Yes, programmable (comm.)

± 0.05 % or better

Pt, Balco and Ni RTD

7 differential

2 or 3 wire

150 dB

10 k.

100 dB

#### alog Input

- Accuracy
- Channels
- CMR @ 50/60 Hz
- Input Connections
- Input Type
- Input Impedance
  - NMR @ 50/60 Hz
  - Resolution 16 bits
  - RTD Types and Temperature Ranges

PT-100 RTD		
Pt-50° C	to	150° C
Pt 0° C	to	100° C
Pt 0° C	to	200° C
Pt 0° C	to	400° C
Pt-200° C	to	200° C
EC RTD 100	ohms.= 0.0	0385)
JIS RTD 100	ohms.= 0.0	0392)
Pt 1000 RTD: Pt	-40 ~ 160°	С
Balco 500 R1	D: -30 ~ 12	20° C
Ni 518: -80 ~ 10	0° C	
Ni 518: 0 ~ 100°	С	

- Sampling Rate
- Span Drift
- Zero Drift

#### Protection

Individual Wire Burn-out Detection

## **Ordering Information**

- ADAM-6015
- 7-ch RTD Input Module

10 samples / sec.

± 25 ppm/° C

± 3 µV/° C

Protection 2,000 V<sub>DC</sub>

20 ~ 95% RH	
(non-condensing)	
0~95% RH	
(non-condensing)	
-10 ~ 70° C	
-20 ~ 80° C	

	Ge
2.5 W @ 24 Vdc	•
Yes, programmable (Comm.)	•
	An
6 DI	•
Logic level 0: close to	
GND	

GND Logic level 1: open Logic level 0: +3 V max Logic level 1: 10 ~  $30 V_{DC}$ 

6 Relay AC: 250 V @ 5 A 30 V @ 5 A

500 V<sub>AC</sub> (50/60 Hz) 7 ms 3 ms

1G. min. at 500 V<sub>DC</sub> Protection

6-ch Digital Input/Power

10 ms

## ADAM-6017 ADAM-6018 ADAM-6024

8-ch Analog Input w/DO Module

8-ch Thermocouple Input w/DO Module

12-ch Universal Input/Output Module



ADVANTECH 5-17 9200-www.stevenengineering.com

## **ADAM-6022**

## **Ethernet-based Dual-loop PID Controller**



**C€ FCC** 

for each control loop)

10/100Base-T

±0.1 % or better 13.1 Hz @ 50 Hz

15.72 Hz @ 60 Hz

 $0 \sim 10 V_{DC}, 0 \sim 20 mA$ , 4 ~ 20 mA

6 differential

16 bits

±6 µV/° C

0.05% of FSR

±50 ppm/° C

0 ~ 20 mA

12 bits

2

15 V<sub>DC</sub> (current output)

 $0 \sim 10 V_{DC}$ ,  $4 \sim 20 mA$ ,

20 M

## **Specifications**

#### General

- Power Consumption 4 W @ 24 Vdc Loop Number 2 (3 AI, 1 AO, 1 DI, 1 DO
- LAN

#### **Analog Input**

<ul> <li>Accuracy</li> </ul>	
------------------------------	--

- Bandwidth
- Channels
- CMR @ 50/60 Hz 92 dB min.
- Resolution
- Input Impedance
- Input Range
- Isolation Voltage
- $2,000 V_{DC}$  Sampling Rate 10 samples/sec. ±25 ppm/° C

1

2

- Span Drift
- Zero Drift

#### **Analog Output**

- Channels
- Accuracy
- Channels
- Drift
- Drive Voltage
- Output Range
- Resolution

#### **Digital Inputs**

- Channels
- Open Collector to 30 V 100 mA max. load 300 mW 2,000 V<sub>DC</sub>
- Isolation Voltage
- Fault and Overvoltage Withstands overvoltage overvoltage Power Reversal Protection
- Protection up to  $+/-35 V_{DC}$





PANEL MOUNTING BRACKET



DIN - RAIL MOUNTING ADAPTER

0~95% RH.

(non-cond.)

#### **Digital Outputs**

- Channels
- Open Collector to 30 V 100 mA max. load
- Fault and Overvoltage Withstands overvoltage Protection up to +/-35 V<sub>DC</sub>

#### Environment

- Humidity (Operating) 20~95% RH. (non-cond)
- Humidity (Storage)
- Operating Temperature  $-10 \sim 50^{\circ} \text{ C}$
- Storage Temperature -20 ~ 80° C



## **Ordering Information**

ADAM-6022

Dual-loop PID

Controller

5-18 AD\+NTECH Ethernet I/O Modules Courtesy of Steven Engineering, Inc.-230 Ryan Way, South San Francisco, CA 94080-6370-Main Office: (650) 588-9200-Outside Local Area: (800) 258-9200-www.stevenengineering.com

2

## **Breaking Through with Open HMI Solutions**



## **Open HMI, Unlimited Potential**

Advantech's vision is to become the leading HMI platform provider in the PC-based industrial automation market by creating value-added, standard product solutions and by offering customization to meet unique requirements. We offer a wide range of HMI products for automation needs, including; hardware platforms such as the industrial panel PC's (IPPC), industrial workstations (AWS), flat panel monitors (FPM), and the touch panel computers (TPC). We also offer very powerful NT/CE and Linux-based HMI solutions to easily migrate applications up or down as scope changes.

Open HMI operates with a scalable (and open) operating system (providing standard file formats, interfaces and communications) and can provide some PC-based functionality, such as increased information processing. These are diskless and fanless products that offer advanced functionality over traditional HMI products with improved data handling and standard interfaces and communications.

## **Applications:**

- Environmental Monitoring
- Facility Management
- Machine Automation
- Factory Automation
- Building Automation



Open HMI Provides an Open & Integrated Platform to Simplify System Architectures and Reduce System Maintenance Costs

## **Touch Panel Computers (TPC)**

#### Compact & Rugged HMI Platforms for Seamless Interaction between Humans and Machines

The ultra-slim, light, fanless and vibration-resistant design of Advantech's TPC Series provides an ideal HMI platform for most automation applications. TPC products are available in display sizes of 5.7", 6.4", 10.4", 12.1", and 15". TPC's feature processors that are low in power consumption, and they also have a unique fanless design. With their stable system architecture, TPC is an ideal solution for any industrial environment. In addition, the product housings are made from a Aluminum-Magnesium Alloy which results in a lightweight unit, with corrosion resistance and excellent heat dissipation.

## **Industrial Panel PCs (IPPC)**

#### Powerful Computing and Robust Platforms with High Performance for Factory Floors

Advantech's IPPC series has proven their reliability through years of operation in all parts of the world. They can be built to achieve a performance and cost ratio that is optimum for any industrial application. Constructed with stainless steel chassis and heavy-duty aluminum front panels, the rugged design of Advantech's IPPC series can withstand tough industrial environments. Equipped with powerful Intel Pentium III & 4 processors, the IPPC has high computing power, and also provides expansion slots for add-on boards. The IPPC can be configured with memory, drives, and operating systems that meet your diverse needs.



#### **Flat Panel Monitors (FPM)**

## Full Range of Industrial-grade Units with Multifunction Capabilities and Brilliant Displays

Advantech's flat panel monitors are designed specifically for industrial environments. These monitors feature industrial-grade flat panel LCDs with brightness that is often more than twice that of commercial monitors, making them much easier to see. FPM products are designed for factory floor environments and can withstand the higher temperatures, vibration, and the dirt and dust that can be commonplace. High NEMA and IP ratings for the bezel design enable these products to be installed in wet and dusty areas. A full-range selection is provided in sizes ranging from 6", 12",15", 17" to 19".



## Industrial Workstations (ATM & AWS)

## Heavy-duty, Expandable & Reliable Solutions to Optimize Site Operations and Visualization

Advantech provides a series of powerful industrial workstations with open architecture that incorporates widely used PC technology for industrial platforms. The compact and heavy-duty industrial workstations are specially designed for controlling machinery or processes; displaying the information necessary to repair, maintain, or starting up a process, and gathering basic production information for making informed business decisions. The AWS Series provides multiple CPU choices, and supports different PCI/ISA passive backplanes. In addition, our ATM series integrates TFT-LCD display, built-in keyboard, touchpad, and front access/wiring and chassis in one box. The all-in-one design gives great benefits in test and measurement application.

