

PANELSTATION

QuickDesigner® - Compatible Operator Interface



[Corporate Overview](#)

[The Original Operator Interface](#)

[QuickDesigner Software](#)

[PanelStation Product Line](#)

[PLC Cables and Accessories](#)

[QuickPanel Migration Options](#)

[Global Value, Service
and Investment Protection](#)

[Worldwide Support](#)



The Best in Human Machine Interfaces



Pro-face offers you the best solutions for all your application needs

- ✓ Low Maintenance Industrial Computers
- ✓ Remote Maintenance and Monitoring HMI Solutions
- ✓ Factory and Office HMI Data Sharing Solutions
- ✓ Machine Cost Reduction HMI Solutions
- ✓ Ultra-clear Long-life Touch Screen Monitors

About Us

Pro-face is a global supplier of a broad range of plant visualization and control solutions for industrial automation markets. We offer dedicated and PC-based open HMI solutions designed to increase machine and plant efficiency while reducing overall system costs. Our principal products include Pro-face brand operator interfaces, industrial PCs and HMI software plus Xycom brand industrial computers and monitors.

Pro-face America, headquartered in Saline, Michigan is the North American sales office. Pro-face products are supported by 17 major offices with over 1200 representatives around the world.

Innovative

- #1 in delivering lowest cost of product ownership
- #1 in maintaining panel cutout compatibility 20+ years
- #1 in HMI hardware and data connectivity
- First to deliver industrial flat panel operator interface touch screens
- Manufacturer of the original QuickPanel®

Proven

- 35+ years of industrial HMI solutions
- Over 1.5 million operator interfaces in use today
- Installed in more than 300,000 factory-floor systems worldwide
- Serving 50 countries and expanding

Trusted

Pro-face is installed in the world's most recognized manufacturing facilities.

Find us here (and other places):

Industrial Automotive	Food & Beverage	Agriculture
Packaging	Material Handling	Oil & Gas
Water/Wastewater	Semiconductor	Power Generation

Industry leading technology solving today's toughest factory problems.

PanelStation HMI Operator Interface Series

QuickDesigner Compatible Operator Interfaces,



from the manufacturer...

Pro-face is the most recognized and trusted name in operator interfaces and graphic controllers worldwide.

In 2003, Pro-face began marketing its own brand of operator interface products in North America. The Pro-face PanelStation product line was created to maintain, support and service the existing installed base of Pro-face products. Pro-face PanelStation operator interface products are 100% equivalent to GE Fanuc's QuickPanel products and share the same part numbers.

Featuring sizes from 6" to 12.1," and now available in Ethernet-ready versions, PanelStation bridges the gap between text-based message displays and full-featured graphics touch screens.

...and in stock.

QuickDesigner 3.7 Graphical HMI Editing Software



Simple, easy-to-learn HMI development for all PanelStation models

- Windows®-based (95, 98, 2000 only)
- Friendly and easy-to use
- Common to all PanelStation models
- Compatible with all QPJ, QPK, QPI, QPL and QPM models

QuickDesigner features a comprehensive set of functional panel operators

- **Push buttons** toggle on and off at a touch
- **Selector switches**
- **Pilot lights** glow to indicate active status and feature text and numeric data displays
- **Bar-graph displays**
- **Images:** Static and dynamic bitmapped or object-oriented







Do you need to upgrade to QuickDesigner 3.7? Older-version software can lead to hardware compatibility issues. Use our web site to get the latest service packs free of charge. Note: This software does not support GE protocol drivers.

Order Number	Description
QDA-EDT-001	QuickDesigner 3.7 software w/ GPW-CB02 RS232 program cable
QDA-EDT-001/L	QuickDesigner 3.7 software - no download cable

QuickPanel and QuickDesigner are registered trademarks of GE Fanuc Automation North America Inc.

PanelStation Series HMI Operator Interface

PanelStation Series Lineup

<div>12.1 inch</div> <div></div>		<div>10.4 inch</div> <div></div>		<div>9 inch</div> <div></div>		<div>7.4 inch</div> <div></div>	
<div>Display</div> <div>■TFT color SVGA (65K colors)</div> <div>■Resolution: 800 x 600</div> <div>Functional Specifications</div> <div>■4MB Flash EPROM for large applications</div> <div>■Ethernet: 10Base-T</div> <div>■Printer port</div> <div>■CompactFlash™ storage</div> <div>■Two serial ports</div> <div>■One download/bar-code port</div> <div>■Auxiliary I/O: Remote reset input, system alarm output, speaker output, sound lineout, buzzer output</div> <div>■Power: 85-132V AC (50VA) or 24V DC (50W)</div> <div>Environmental</div> <div>■Operating temperature: 0° to 50° C</div> <div>■Storage temperature: -20° to 60° C</div> <div>■Ratings: NEMA 4x/12, IP65f</div> <div>■Humidity: 10-90% RH non-condensing</div> <div>■External dimensions: W317mm [12.48in] H243mm [9.57in] D58mm [2.28in]</div> <div>■Cutout: W301.5mm [11.87in] H227.5mm [8.96in]</div> <div>■Weight: 7.7 lbs (3.5kg)</div> <div><div>AC 100-240V</div><div>UL c UL CE</div><div>DC24V</div><div>UL c UL CE</div></div>		<div>Display</div> <div>■TFT color VGA (65K colors)</div> <div>■Resolution: 640 x 480</div> <div>Functional Specifications</div> <div>■4MB Flash EPROM for large applications</div> <div>■Ethernet: 10Base-T</div> <div>■Printer port</div> <div>■CompactFlash™ storage</div> <div>■Two serial ports</div> <div>■1 download/bar-code port</div> <div>■Auxiliary I/O: Remote reset input, system alarm output, speaker output, sound lineout, buzzer output</div> <div>■Power: 85-132V AC (50VA) or 24V DC (50W)</div> <div>Environmental</div> <div>■Operating temperature: 0° to 50° C</div> <div>■Storage temperature: -20° to 60° C</div> <div>■Ratings: NEMA 4x/12, IP65f</div> <div>■Humidity: 10-90% RH non-condensing</div> <div>■External dimensions: W317mm [12.48in] H243mm [9.57in] D58mm [2.28in]</div> <div>■Cutout: W301.5mm [11.87in] H227.5mm [8.96in]</div> <div>■Weight: 7.7 lbs (3.5kg)</div> <div><div>AC 100-240V</div><div>UL c UL CE</div><div>DC24V</div><div>UL c UL SF CE</div></div>		<div>Display</div> <div>■Monochrome amber electroluminescent</div> <div>■Resolution: 640 x 400</div> <div>Functional Specifications</div> <div>■2MB Flash EPROM</div> <div>■Ethernet: 10Base-T</div> <div>■Printer port</div> <div>■CompactFlash™ storage</div> <div>■1 serial port</div> <div>■1 download/bar-code port</div> <div>■Power: 24V DC (22W)</div> <div>Environmental</div> <div>■Operating temperature: 0° to 50° C</div> <div>■Storage temperature: -10° to 60° C</div> <div>■Ratings: NEMA 4x/12, IP65f</div> <div>■Humidity: 210-85% RH non-condensing</div> <div>■External dimensions: W274mm [10.79in] H216mm [8.5in] D56.5mm [2.23in]</div> <div>■Cutout: W259mm [10.2in] H201mm [7.92in]</div> <div>■Weight: Less than 2.5kg</div> <div><div>AC 100-240V</div><div>UL c UL CE</div><div>DC24V</div><div>UL c UL SF CE</div></div>		<div>Display</div> <div>■TFT color VGA (65K colors)</div> <div>■Resolution: 640 x 480</div> <div>Functional Specifications</div> <div>■4MB Flash EPROM for large applications</div> <div>■Ethernet: 10Base-T</div> <div>■Printer port</div> <div>■CompactFlash™ storage</div> <div>■Two serial ports</div> <div>■1 download/bar-code port</div> <div>■Auxiliary I/O: Remote reset input, system alarm output, speaker output, sound lineout, buzzer output</div> <div>■Power: 24V DC (28W)</div> <div>Environmental</div> <div>■Operating temperature: 0° to 50° C</div> <div>■Storage temperature: -20° to 60° C</div> <div>■Ratings: NEMA 4x/12, IP65f</div> <div>■Humidity: 10-90% RH non-condensing</div> <div>■External dimensions: W215mm [8.46in] H170mm [6.69in] D60mm [2.36in]</div> <div>■Cutout: W204.5mm [8.05in] H159.5mm [6.28in]</div> <div>■Weight: 5.5 lbs (2.5kg)</div> <div><div>AC 100-240V</div><div>UL c UL CE</div><div>DC24V</div><div>UL c UL SF CE</div></div>	
Display Size	12.1"		10.4"		9"		7.4"
Display Type	TFT		TFT		Amber Monochrome		TFT
Rated Voltage	AC85-132V	DC24V	AC85-132V	DC24V	85-132V AC (50VA)	24VDC (50W)	DC24V
Order Number	QPL-CTAE-0000	QPL-CTDE-0000	QPI-CTAE-0000	QPI-CTDE-0000	QPI-31200-E2P	QPI-3D200-E2P	QPG-CTDE-0000

Communication Modules

For all QPJ and QPK units	For 9" QPI-3x200-E2P units	For Ethernet-based QPG/QPI/QPL-CTxE-0000 units
QPJ-ABD-201¹ A-B Data Highway Plus interface module (UL, CE)	QPI-ABD-201 A-B Data Highway Plus interface module (UL, CE)	QPI-ABD-201² A-B Data Highway Plus interface module (UL, CE)
QPJ-ABR-201¹ A-B 1771 Remote I/O interface module (UL, CE)	QPI-ABR-201 A-B 1771 Remote I/O interface module (UL, CE)	QPI-ABR-201² A-B 1771 Remote I/O interface module (UL, CE)
QPJ-MBP-XA1 Modbus Plus interface module (UL)	QPI-MBP-XA1 Modbus Plus interface module (UL)	CA3-MBPALL-41 Modbus Plus interface module compatible with CTDE/CTAE HMI units
QPJ-PBS-201¹ Profibus interface module	QPI-PBS-201 Profibus interface module	QPI-PBS-201² Profibus interface module
CA3-MBPALL-41 Modbus Plus interface module for QPK-STDN-0000 and QPK-CTDE-0000	QPI-DVN-202 DeviceNet interface module	QPI-DVN-202² DeviceNet interface module
QPJ-DVN-202¹ DeviceNet interface module		

¹Requires PSM-CONV00 adapter to use with QPK-STDN-0000 and QPK-CTDE-0000 units

²Requires PSL-CONV00 adapter to use with QPG/QPI/QPL-CTxE-0000 units

Protocols Supported by QuickDesigner 3.7

Allen-Bradley
SLC-500 single-point, network channel 0 and DF1
PLC-5 channel 0 DF1 serial
PLC-2 program port
Remote I/O
Data Highway Plus for PLC5 and SLC 5/04
Aromat (MEWNET)
ASCII slave for computer communications
B & R Mininet
CANopen
DeviceNet
Flex (ASCII)
Hitachi H Series, Hitachi S10
Idec Micro 1, Micro 3, FA2J, FA3S
Interbus-S
Keyence KV-L2 port 1, KV-L2 & KV-10R program port
Koyo DL405, DL305, DL205

Mitsubishi
A Series computer interface
A Series program port
FX Series program port
Modicon Modbus Master, Modbus Plus, Modbus Slave
Omron C Series host link
PLC Direct
Profibus-DP
Siemens S5 family program port
S7-200 PPI, S7-300/400 MPI
3964R communication link
Simatic T1405/305 CCM2,
TI500 Series program port
Square D Symax program port or NIM
Toshiba T1, T2, MX and EX
Toyopuc PC1 and PC2
Unitelway

6 inch

**Display**

- TFT color (65K colors) or STN color (4,096 colors)
- Resolution: 320 x 240

Functional Specifications

- 2MB Flash EPROM (CTDE)
- 1MB Flash EPROM (STDN)
- Ethernet: 10Base-T
- CompactFlash™ storage
- 2 serial ports, 1 printer port
- 1 download/bar-code port
- Power: 24V DC (22W)

Environmental

- Operating temperature: 0° to 50° C
- Storage temperature: -20° to 60° C
- Ratings: NEMA 4x/12, IP65f
- Humidity: 10-90% RH non-condensing
- External dimensions:
W171mm [6.73in]
H138mm [5.43in]
D60mm [2.36in]
- Cutout: W156mm [6.14in]
H123mm [4.86in]
- Weight: 2.6 lbs (1.2kg)



6-inch Mini

**Display**

- Blue/white LCD
- Resolution: 320 x 240
- 16W x 12H resistive touch screen

Functional Specifications

- 1MB Flash EPROM
- One RS-232/RS-422 port
- 1 download/bar-code port
- Power: 24V DC (20W)

Environmental

- Operating temp: 0° to 50° C
- Storage temp: -20° to 60° C
- Ratings: NEMA 4x/12, IP65f (front panel)
- Humidity: 20-85% RH non-cond.
- External dimensions:
W207mm [8.15in]
H157mm [6.18in]
D58mm [2.28in]
- Cutout dimensions:
W192mm [7.56in]
H142mm [5.59in]
- Weight: 1.1 kg



Display Size	6"		6" Mini
Display Type	TFT	STN	LCD Blue/White
Rated Voltage	DC24V	DC24V	DC24V (20W)
Order Number	QPK-CTDE-0000	QPK-STDN-0000	QPM-3D200-B2P

Technical Questions?

Answers to your technical questions are at your fingertips. Visit the online Support Center Knowledge Base at www.profaceamerica.com.

PanelStation Warranty

All PanelStation Series brand products are warranted by Pro-face to be free from defects of material and workmanship under normal use and service for a period of two years from shipment. Extended warranties are available. Contact Pro-face for details.

Accessories

Additional accessories are available for PanelStation Series brand products. Ask for a complete listing of available products.

PanelStation AB HMI Kits			
ABK-STDN-0000/SER	6" STN Serial 24VDC	ABK-CTDE-0000/ABD	6" TFT w/AB DH+, 24VDC
ABK-STDN-0000/ABD	6" STN w/AB DH+, 24VDC	ABK-CTDE-0000/ABR	6" TFT w/AB RIO, 24VDC
ABK-STDN-0000/ABR	6" STN w/AB RIO, 24VDC	ABK-CTDE-0000/DVN	6" TFT w/AB DeviceNet, 24VDC
ABK-STDN-0000/DVN	6" STN w/AB DeviceNet, 24VDC	ABI-CTDE-0000/ABR	10.5" TFT Ethernet w/AB RIO, 24VDC
ABK-CTDE-0000/SER	6" TFT Serial 24VDC		

PLC Cables

All cables are 12 feet long except as noted.

Mfr.	PLC Type	Description	Order No.
Allen-Bradley	SLC 500, 5/01, 5/02, 5/03	DH-485 program port	HMI-CAB-C83
	SLC 500, 5/01, 5/02, 5/03	DH-485 link, 6-ft. max, via 1747-A/C module, multiple units to multiple SLCs	HMI-CAB-C84
	SLC 5/03, SLC 5/04	SLC, 9-pin RS-232	HMI-CAB-C52
	PLC-5	SLC, 25-pin RS-232	HMI-CAB-C53
	PLC-2	Prog. port, 15-pin RS-422	HMI-CAB-C90
Micrologix	Program port, 8-pin circular DIN RS-232		HMI-CAB-C106
	Remote I/O	See Communication Modules (page 4)	
Data Highway Plus		See Communication Modules (page 4)	
ASCII Communications	RS-232	HMI to RS-232 screw terminal serial port	HMI-CAB-C232
	RS-422	HMI to RS-422 screw terminal serial port	HMI-CAB-C422
DeviceNet	DeviceNet	See communication modules	
GE Fanuc	90/30, 90/70 PLC	RS-422 program port via 15-pin D-sub	HMI-CAB-C82
	SNP protocol PLC	CMM module via RS-232 25-pin D-sub	HMI-CAB-C53
Generic PLC Cables & Adapters		PLC CMM module via RS-422 25-pin D-sub	HMI-CAB-C93
	RS-232	Connects HMI to PLC RS-232 via open wires	HMI-CAB-C232
	RS-232C	Cross-type 2-pin D-sub connector both ends (5M)	GP410-IS00-0
	RS-232C	Straight cable w/25-pin D-sub both ends (5M)	GP410-IS01-0
	RS-422	Connects HMI to PLC RS-422 port via open wires	HMI-CAB-C422
	RS-422	Serial 25-pin D-sub connector to 9-pin D-sub (5M)	GP230-IS11-0
	RS-422	Multi-link 25-pin D-sub connector to 9-pin D-sub (5M)	GP230-IS12-0
	Adapter RS-422	25-pin D-sub to screw terminal adapter	GP070-CN10-0
IDEC	Micro-1, FA via link adapter	25-pin RS-232	HMI-CAB-C53
	Micro 3	25-pin to 9-pin RS-232	HMI-CAB-C109
Keyence	KV-L2 port 1	25-pin RS-232	HMI-CAB-C53
Koyo/PLC Direct	DL430, DL440 P2, D4-DCM, DL330, DL350 port 2, DL450P Port A	RS-232 25-pin D-sub port	HMI-CAB-C53
	DL330P with use of D3-232 DCU	RS-232 25-pin D-sub port	HMI-CAB-C53
	DL250 port 1/DL350 port 1, DL240 port 2 PLCs	RS-232 via 6-pin modular phone	HMI-CAB-C86
	Series A1S	9-pin RS-232 D-sub for A1SJ71C24-R2	GP000-IS02-MS
	Series A computer interface	25-pin RS-232 D-sub	HMI-CAB-C53
	Series A FX, FX0 program port	25-pin RS-422 (FX0 via adapter)	HMI-CAB-C91
	A/QnA/FX series	2-port adapter II	GP070-MD11
		Adapter cable RS-422, 5m, for 2-port adapter II	GP070-MDCB11
	FX, FX0	Programming port	GP430-IP10-0
	FX, FX0	FX programming port	GP430-IP11-0
Modicon	984 A, B, X	25-pin D-sub RS-232	HMI-CAB-C53
	984 slot and compact	9-pin D-sub RS-232	HMI-CAB-C58
	984 micro	RJ45 headset conn. RS-232	HMI-CAB-C102
	MODBUS Plus	See Communication Modules (page 4)	
Omron	C200H	25-pin RS-232	HMI-CAB-C53
	C20H, CQM1	9-pin D-sub RS-232	HMI-CAB-C67
PLC Direct	CS1	25-pin D-sub	GP000-IS03-MS
	See Koyo/PLC Direct		
PROFIBUS		See Communication Modules (page 4)	
Reliance	Automate program port, R-net gateway	25-pin D-sub RS-232	HMI-CAB-C53
Siemens	S5 family program port	15-pin current loop	HMI-CAB-C76
	S7-200 PPI	9-pin RS-422	HMI-CAB-C110
Simatic TI	MPI cable	via MPI connection	GP070-MPI-41
	305 used with RS-232 DCU; 405, 500 series w/25-pin prog. port	25-pin RS-232	HMI-CAB-C53
	500 series, 9-pin male RS-422	9-pin RS-422 D-sub	HMI-CAB-C92
	505 series, 9-pin prog. port	9-pin RS-232 D-sub	HMI-CAB-C101
Square D	Symax 100 & greater	9-pin D-sub RS-422	HMI-CAB-C94
	Symax 50 via link adapter P1	25-pin D-sub RS-232	HMI-CAB-C53
Toyopuc	PC2F	half-duplex 4-spade lugs RS-422	HMI-CAB-C114
Uni-Telway	TSX37 Series	25-pin to 8-pin male mini-DIN	HMI-CAB-C116

Refer to Pro-face Operator Interface and Controller Products 2009 Selection Guide guide for further information.

Migration Options

Stay Confident, Keep the Reliability

Investment Protection for QuickPanel® Users

Are you being pushed to migrate?

Is migrating to a new HMI platform in your company's best interest?

Most Importantly, Are you ready?

Look to Pro-face to provide you a choice.



Option 1 Buy PanelStation Operator Interfaces



Keeping it Simple

- ✓ No project migration
 - Use your existing QuickDesigner Software
 - Use your existing part numbers
- ✓ No certification issues
- ✓ 20+ years cutout compatibility
- ✓ Free phone technical support
- ✓ Access to vast online knowledge-base and learning center
- ✓ 5-day turnaround on repairs

PanelStation = QuickPanel

Option 2 Upgrade to the Latest in HMI Technology



Three Migration Steps:

- ① Convert, ② Import, ③ Download

Why Migrate?

- ✓ One development software, endless HMI solutions
- ✓ Choice of platforms: Windows®-based or dedicated operator interfaces
- ✓ Cut machine costs: single unit HMI plus PLC options
- ✓ Full Internet-based remote servicing tools
- ✓ More connectivity – motion, drivers, scanners, PLCs, PACs, DCS

Make Pro-face your last HMI conversion!



Tools for Our Customers

Access Our Online Knowledge Base and Learning Center and Download

- ➔ Latest QuickDesigner Service Packs
- ➔ Migration Guide and Reference Charts
- ➔ Frequently Asked Questions
- ➔ Manuals and Datasheets

Get GP-Pro EX for FREE!

AGP3000 First Time Buyers Promotion

- **FREE** - GP-Pro EX software
- **FREE** - programming cable

With your first purchase of select AGP3000 Series PCs.

To learn more...

go to www.profaceamerica.com/uncover



Choices, It's what you expect from a global supplier.

Experience Pro-face Global Value, Service and Investment Protection



The Pro-face Product Value

■ Expert Training and Online Resources

Instructor-led HMI Training

- On-site self-paced product training
- HMI competency skills building
- HMI efficiency tips and tricks

24/7 Knowledge-Base & Learning Center Access

- Extensive product resource center (Otasuke Pro)
- Manuals/datasheets/updates/demos/FAQs
- Self-paced training and learning resources

■ Unsurpassed Investment Protection

Phone-in PriorityTech Support

- Global product support network
- 20+ years cutout compatibility
- 7 year factory service and support
- 5-day repair turnaround (Priority 1-day upon request)

■ Outstanding Value and Service

- ONE development software for open and dedicated HMI products
- No charge for HMI communication drivers
- Conversion and product migration assistance

■ Exceptional Support

Phone-in PriorityTech Support

- No contracts, no hassles
- Direct connect to live product support specialists
- +95% problem resolution and callback in 24 hr

On-site HMI Application Assistance

- Highly trained field technical specialist
- Proof-of-concept assistance

Remote HMI Application Engineer


- Real-time HMI troubleshooting services
- HMI project file analysis with simulation



Delivering more than a box

Pro-face America
 750 North Maple Road
 Saline, MI 48176 USA
 Tel: 734-429-4971 or
 Toll Free: 800-289-9266
 Fax: 734-429-1010
<http://www.profaceamerica.com>
 E-mail: sales@profaceamerica.com

Customer Care Center:
 Tel: 734-944-0482
 Web Support: <http://support.profaceamerica.com>
 E-mail: customercenter@profaceamerica.com



Globally Recognized, Globally Trusted, Globally Supported

Global Head Office

Digital Electronics Corporation
 Osaka, JAPAN
 Tel: +81 (0)6 6613 3116
 Fax: +81 (0)6 6613 5888
<http://www.pro-face.com>
info@pro-face.com

North/South American Head Office

Pro-face America, Inc.
 Saline, MI U.S.A.
 Tel: +1 734 429 4971
 Fax: +1 734 429 1010
<http://www.profaceamerica.com>
sales.info@profaceamerica.com

European Head Office

Pro-face Europe B.V.
 Hoofddorp, THE NETHERLANDS
 Tel: +31 (0)23 55 44 099
 Fax: +31 (0)23 55 44 090
<http://www.pro-face.com>
info@pro-face.com

France

Pro-face France S.A.S.
 Mitry-Mory, FRANCE
 Tel: +33 (0)1 60 21 22 91
 Fax: +33 (0)1 60 21 22 92
<http://www.pro-face.fr>
sales@pro-face.fr

Poland

Pro-face Europe B.V. (Warsaw Office)
 Warszawa, POLAND
 Tel/Fax: +48 (22) 465-66-62
<http://www.pro-face.pl/>
proface@pro-face.pl

Switzerland

Pro-face Deutschland GmbH
 Regensdorf, SWITZERLAND
 Tel: +41 (0)43 343 7272
 Fax: +41 (0)43 343 7279
<http://www.pro-face.ch>
info@pro-face.ch

Australia and New Zealand

Pro-face Australia Pty Ltd.
 Melbourne, AUSTRALIA
 Tel: +61 (0)3 9550 7395
 Fax: +61 (0)3 9550 7390
<http://www.pro-face.com.au> <http://www.pro-face.co.nz>
info@pro-face.com

South-East Asia Pacific

Pro-face South-East Asia Pacific Co., Ltd.
 Bangkok, THAILAND
 Tel: +66 (0)2 617 5678
 Fax: +66 (0)2 617 5688
<http://www.pro-face.co.th>
support@pro-face.co.th

Austria

Pro-face Europe B.V. (Austria Office)
 Hagenberg, AUSTRIA
 Tel: +43 7236 3343-520
 FAX: +43 7236 3343-529
<http://www.pro-face.at>
office@pro-face.at

Germany

Pro-face Deutschland GmbH
 Solingen, GERMANY
 Tel: +49 (0)212 258 260
 Fax: +49 (0)212 258 2640
<http://www.pro-face.de>
sales@pro-face.de

Scandinavia, Baltic Countries

Pro-face Northern Europe ApS
 Roskilde, DENMARK
 Tel: +45 70 22 01 22
 Fax: +45 70 22 01 33
<http://www.pro-face-eu.net/>
info@pro-face.dk

United Kingdom

Pro-face UK Ltd
 Coventry, ENGLAND
 Tel: +44 (0)2476 440088
 Fax: +44 (0)2476 440099
<http://www.pro-faceuk.com>
info@pro-faceuk.com

China

Pro-face China International Trading (Shanghai) Co., Ltd.
 Shanghai, P. R. CHINA
 Tel: +86 (0)21 6361 5175
 Fax: +86 (0)21 6361 5176
<http://www.pro-face.com.cn>
proface@pro-face.com.cn

South Korea

Pro-face Korea Co., Ltd.
 Seoul, SOUTH KOREA
 Tel: +82 (0)2 2630 9850
 Fax: +82 (0)2 2630 9860
<http://www.pro-face.co.kr>
support@pro-face.co.kr

Belgium

Pro-face Europe B.V.
 (Belgium Office)
 +32 (0)52 34 38 70
 +32 (0)52 34 38 71
<http://www.pro-face.be>
belux@pro-face.com

Hungary

Pro-face Europe B.V.
 (Budapest office)
 Szada, HUNGARY
 Tel: +36 28 40 46 55
 FAX: +36 28 40 46 55
tamas@pro-face.com

Spain and Portugal

Pro-face España
 Cardedeu (Barcelona), SPAIN
 Tel: +34 (0)93 846 07 45
 Fax: +34 (0)93 845 48 68
<http://www.pro-face.es>
central@pro-face.es

Russia

Pro-face Northern Europe ApS (Saint-Petersburg office)
 Saint-Petersburg, RUSSIA
 Tel: +007 (812) 336-47-06
 Fax: +007 (812) 336-47-18
<http://www.pro-face.ru>
info@pro-face.ru

India

Pro-face India
 Bangalore, INDIA
 Tel: +91 80 4011 8050/8033
 Fax: +91 80 4011 8073
sales.proface@proface.co.in

Taiwan

Pro-face Taiwan Co., Ltd.
 Taipei, TAIWAN
 Tel: +886 (0)2 2657 1121
 Fax: +886 (0)2 2657 1021
<http://www.pro-face.com.tw>
proface@pro-face.com.tw

Czech Republic

Pro-face Europe B.V. (Czech Republic Office)
 Štěrbovice, CZECH REPUBLIC
 Tel: +420 373 721 214
 Fax: +420 373 721 214
<http://www.pro-face.cz/>
brynda@pro-face.cz

Italy

Pro-face Italia S.p.A.
 Bovisio Masciago (Milano), ITALY
 Tel: +39 0362 59 96 91
 Fax: +39 0362 59 96 99
<http://www.pro-face.it>
info@pro-face.it

Sweden

Pro-face Sweden AB
 Löddeköpinge (Malmö), SWEDEN
 Tel: +46 46 540 90 70
 Fax: +46 46 71 27 90
<http://www.pro-face-eu.net>
info@pro-face.se

Contact your local distributor today: