

Proximity magnetic sensors, rectangular

Rectangular			
Types	S series	SPB2 series	SPA1 series
			
Dimensions (mm)	11.5 x 79 x 21.2	25.5 x 85 x 24	16 x 90 x 20
Electrical specifications			
Max. switch. voltage contact	250 VAC [SA / SC 2, SB2 / -S5] 1500 VAC [SA / SC 8] 230 VAC [SS2, S.BS.2]	250 VAC	24 VDC [output 1 and 2]
Max. switch. current contact	1 A [SS2, S.BS.2] 3 A [SA2, SC2, SB2, SB2S5, SA8, SC8]	3 A	0.5 A [output 1] 4 A [output 2]
Max. switch. power contact	100 VA [SA / SC 2, SB2 / -S5] 120 VA [SA / SC 8] 60 VA [SS2, S.BS.2]	100 VA	5 VA [output 1] 100VA [output 2]
Power supply			24 VDC
General specifications			
Operating distance	5 - 32 mm	5 - 30 mm	12 mm
Output connection	PVC cable, 0.5 m (0.24 m Type S5)	Faston [SPB2] 2 m PVC Cable [SPB22MT]	PVC cable, 19 cm Pig-tail
Degree of protection	IP 67	IP 67 [SPB22MT] IP 65 [SPB2]	IP 67
Operating temperature	-25°C to +75°C	-25°C to +75°C	-25°C to +80°C
Housing material	Plastic	Plastic	ABS class V0
References			
Normally open	SA2 SA8		
Normally closed	SC2 SC8		
Change - Over	SS2		
Bistable	SB2 SB2S5	SPB2 SPB22MT	
Bistable CO	S.BS.2		
Normally closed, 2 outputs			SPA1S2 SPA1S3

Proximity magnetic sensors, rectangular

Rectangular		
Types	M and MS series	MM series
		
Dimensions (mm)	8.3 x 37 x 16	6.1 x 23.5 x 14 [A6] 7 x 27 x 11 [A3, S1]
Electrical specifications		
Max. switch. voltage contact	100 VAC [MS1] 230 VAC [MSA1] 500 VAC [MA3, MC3]	100 VAC [S1, A6] 500 VAC [A3]
Max. switch. current contact	0.25 A [MS1] 0.5 A [MA3, MC3] 0.75 A [MSA1]	0.25 A [S1] 0.5 A [A3, A6]
Max. switch. power contact	5 VA [MS1] 10 VA [MSA1, MA3, MC3]	5 VA [S1] 10 VA [A3, A6]
General specifications		
Operating distance	7 - 35 mm	10 - 40 mm
Output connection	PVC cable, 0.5 m (2 m, Type MSA1)	PVC cable [A3, S1] Twin lead cable [A6]
Degree of protection	IP 67	IP 67
Operating temperature	-25°C to +75°C	-25°C to +75°C
Housing material	Plastic	Plastic
References		
Normally open	MSA1 MA3	MMA3 MMA6
Normally closed	MC3	
Change - Over	MS1	MMS1

Proximity magnetic sensors, cylindrical

Cylindrical

Types	FM... series	FMM... series	FMMP... series
			
Dimensions (mm)	Ø 9.3 [A3, C3, S1] M10 x 0.75 [A3S5, A6] M12 x 1 [C3S1, A9S1]	M8 x 1	Ø 6 x 25 [L25] Ø 6 x 33 [L33] Ø 6 x 38 [L38]
Electrical specifications			
Max. switch. voltage contact	100 VAC [S1, A6] 230 VAC [A9S1] 500 VAC [A3, C3, A3S5, C3S1]	100 VAC [A6, S1] 500 VAC [A3]	140 VAC
Max. switch. current contact	0.25 A [S1] 0.5 A [A3, C3, A6, A3S5, C3S1] 3 A [A9S1]	0.25 A [S1] 0.5 A [A3, A6]	1 A
Max. switch. power contact	5 VA [A3, C3, A3S5, C3S1] 60 VA [A9S1] 100 VA [S1, A6]	5 VA [S1] 10 VA [A3, A6]	10 VA
Max carry current			1.2 A
General specifications			
Operating distance	5 - 36 mm	8 - 27 mm	> 8 mm
Output connection	PVC cable 0.5 m for Ø 9.3 2 m for M10 and M12	PVC cable, 2 m	Twin lead cable, 0.5 m
Degree of protection	IP 67	IP 67	IP 67
Operating temperature	-25°C to +75°C	-25°C to +70°C	-20°C to +75°C
Housing material	Plastic [A3, C3, S1] Nickel plated brass [A6] Brass [A3S5, C3S1, A9S1]	Stainless steel [A3, S1] Nickel plated brass [A6]	Plastic
References			
Normally open	FMA3 FMA3S5 FMA6 FMA9S1	FMA3 FMA6	FMMPA7L25 FMMPA7L33 FMMPA7L38
Normally closed	FMC3 FMC3S1		
Change - Over	FMS1	FMMS1	

Proximity magnetic sensors, cylindrical

Cylindrical

Types	FMP... series	FS... series	FSLP... series	FSM... series
				
Dimensions (mm)	M12 x 1 x 100	Ø 13.5 [A2, A8, C2, C8, S2] M10 x 1.25 [A2S3, S2S1] M12 x 1 [A2S4, S2S4] M16 x 1.5 [B2]	Ø 16	M12 x 1 [A2, A7, S2] M16 x 1 [S2S2AT]
Electrical specifications				
Max. switch. voltage contact	120 VAC / DC [C7] 175 VDC, 120 VAC [S1] 200 VDC, 140 VAC [A7] 230 VAC / DC [A9, C9, A9S1] 250 VAC / DC [B2]	230 VAC [S2, S2S1, S2S4] 250 VAC [A2, B2, C2, A2S3, A2S4] 1500 VAC [A8, C8]	100 VAC [A7] 250 VAC [B2]	24 VDC [A7] 230 VAC [S2, S2S2AT] 250 VAC [A2]
Max. switch. current contact	0.25 A [S1] 0.5 A [C7] 1 A [A7] 3 A [B2, A9, C9, A9S1]	1 A [S2, S2S4, S2S1] 3 A [A2, B2, C2, A8, C8, A2S3, A2S4]	0.4 A [A7] 3 A [B2]	0.5 A [S2S2AT] 1 A [S2] 3 A [A2] 50 mA [A7]
Max. switch. power contact	5 VA [S1] 10 VA [A7, C7] 60 VA [A9, C9, A9S1] 120 VA [B2]	60 VA [S2S1, S2S4, S2] 100 VA [A2, B2, C2, A2S3, A2S4] 120 VA [A8, C8]	10 VA [A7] 120 VA [B2]	30 VA [S2S2AT] 60 VA [S2] 100 VA [A2] (A7 negligible)
General specifications				
Operating distance	7 - 26 mm	3 - 32 mm	18 - 25 mm (front); >10 - >15 mm (side)	2 - 19 mm
Output connection	PVC cable, 2 m	PVC cable, 2 m 0.5 m for Ø 13.5	PVC cable, 2 m	Silicone cable, 2 m [A7] Silicone cable, 0.5 m [S2S2AT] PVC cable, 2 m [A2, S2]
Degree of protection	IP 67	IP 67	IP 67	IP 67
Operating temperature	-25°C to +75°C	-25°C to +75°C	-30°C to +80°C	-25°C to +75°C [A2, A7, S2] -20°C to +150°C [S2S2AT]
Housing material	Plastic	Plastic [A2, A8, C2, C8, S2, B2] Brass [A2S3 / S4, S2S1 / S4]	Plastic	Brass [S2S2, S2S2AT] Nickel plated brass [A2, A7, S2]
References				
Normally open	FMPA7 [black] FMPA9 [black] FMPA9S1 [black]	FSA2 FSA8 FSA2S32MT FSA2S42MT	FSLPA7	FSMA2 FSMA7
Normally closed	FMPC7 [red] FMPC9 [red]	FSC2 FSC8		
Change - Over	FMPS1 [blue]	FSS2 FSS2S12MT FSS2S42MT		FSMS2 FSMS2S2AT
Bistable	FMPB2 [grey]	FSB22MT	FSLPB2	

Proximity magnetic sensors, slot

Slot

Types

ISY series

IM series



Dimensions (mm)

10 x 45 x 37

7 x 28 x 18.5

Electrical specifications

Max. switch. voltage contact

100 VAC [S1]
500 VAC [C3]

100 VAC [S1]
500 VAC [C3]

Max. switch. current contact

0.25 A [S1]
0.5 A [C3]

0.25 A [S1]
0.5 A [C3]

Max. switch. power contact

5 VA [S1]
10 VA [C3]

5 VA [S1]
10 VA [C3]

General specifications

Output connection

PVC cable, 0.5 m

PVC cable, 0.5 m

Degree of protection

IP 67

IP 67

Operating temperature

-25°C to +75°C

-25°C to +75°C

Housing materials

Plastic

Plastic

References

Normally closed

ISYC3

IMC3

Change - Over

ISYS1

IMS1

Types

Magnetic units CL series

Shapes

Rectangular

Trapezoidal

Cylindrical



General specifications

Minimum separation:

Dimensions (mm)

References

10

25 x 14 x 8

CL1

20

44.5 x 12 x 9

CL2

30

59 x 18 x 9

CL3

50

76 x 25 x 18

CL4

Not mandatory

Dimensions (mm)

References

Dimensions (mm)

References

90 x 31 x 22.5

CL90

Ø 9.3 x 32

CL10

Ø 13.5 x 65

CL11

Ø 18 x 6

CL18

Ø 23 x 9

CL23

Ø 31 x 10

CL31

Ø 20 x 10

CL20S1

Ø 22.1 x 11.3

CL20S3

Level magnetic sensors			
Cylindrical			
Types	ILM series	ILMM series	ILMP series
			
Float Diameter (mm)	Ø 53	Ø 28	Ø 25
Output functions			
	Normally open, Normally closed [2, 8] Change-over [S2]	Normally open and normally closed [5, 590, 5ATS1] Normally open [5S1] Normally closed [5S2, 5S2AT]	Normally open, normally closed
Electrical specifications			
Max. switch. voltage contact	230 VAC [S2] - 250 VAC [2] 1500 VAC [8]	240 VAC, 220 VDC	240 VAC, 200 VDC
Max. switch. current contact	1 A [S2] 3 A [2, 8]	0.5 A	0.5 A
Max. switch. power contact	60 VA [S2] - 100 VA [2] 120 VA [8]	50 VA	50 VA
General specifications			
Output connection	Silicone cable, 0.5 m	XLPE cable, 0.3 m 1,1 m [ATS1]	PVC cable, 0.3 m
Min. liquid specific gravity	0.75 kg / dm ³	0.75 kg / dm ³	
Max. pressure	20 kg / cm ²	10 kg / cm ²	2 kg / cm ²
Degree of protection	IP 67	IP 67	IP 67
Operating temperature	-25°C to +120°C [2, 8, S2]	-10°C to +120°C [5, 590] -10°C to +200°C [5ATS1, 5S2AT] -20°C to +120°C [5S1, 5S2]	-20°C to +80°C
Housing materials	AISI 316 Stainless steel	AISI 304 stainless steel [5, 590 5ATS1] AISI316 stainless steel [5S2AT, 5S1, 5S2]	Plastic
References			
Normally open / Normally closed	ILM.2 ILM8	ILMM5 ILMM590 ILMM5ATS1	ILMP5 ILMP5P
Change - Over	ILMS2		
Normally closed		ILMM5S2AT ILMM5S2	
Normally open		ILMM5S1	

Level magnetic sensors

Cylindrical

Types

ILMPU - ILU - ILMU series

ILSP series

FLM series - Flux Sensors



Float Diameter (mm)	Ø 17.5 [ILMPU] Ø 31 [ILMU] Ø 45 [ILU]	Ø 44	Ø 20
---------------------	---	------	------

Electrical specifications

Max. switch. voltage contact	230 VAC [ILUS2] 240 VAC, 200 VDC [ILMPU5, ILMU5] 250 VAC [ILU2] 1000 VAC [ILU8]	230 VAC [S2] 250 VAC [2] 1500 VAC [8]	100 VAC
Max. switch. current contact	0.5 A [ILMP, ILM] 1 A [ILUS2] 3 A [ILU2, ILU8]	1 A [S2] 3 A [2, 8]	0.4 A
Max. switch. power contact	50 VA [ILMP, ILM] 60 VA [ILUS2] 100 VA [ILU2] 120 VA [ILU8]	60 VA [S2] 100 VA [2] 120 VA [8]	10 VA

General specifications

Output connection	XLPE cable, 0.3 m [ILMPU5] PVC cable, 0.3 m [ILMU5] Silicone cable, 0.5 m [ILU2, ILU8, ILUS2]	Silicone cable, 0.5 m	HT105 PVC cable ended with 6.35 mm female faston
Operating distance Don			+5 mm
Release distance Doff			D _{on} - 2 mm
Min. liquid specific gravity	0.70 kg / dm ³ [ILMPU, ILMU] 0.75 kg / dm ³ [ILU]	0.75 kg / dm ³	
Max. pressure	2 kg / cm ² [ILMPU, ILMU] 100 kg / cm ² [ILU]	0.6 kg / cm ²	
Degree of protection	IP 68	IP 67	IP 67
Operating temperature	-20°C to +80°C [ILMPU, ILMU] -25°C to +100°C [ILU]	-25°C to +100 °C	-30°C to +105°C
Housing materials	Non toxic polypropylene or plastic	Plastic	Stainless steel

References

Normally open / Normally closed	ILMPU5 ILMU5	ILSP2 ILSP8	
Normally open	ILU2 ILU8		FLMA1S1
Change - Over	ILUS2	ILSPS2	