


Digital Flow Switch for Deionized Water and Chemical Liquids

PF2D Series



Body and Sensor

New PFA

Tube

Super PFA

Three types of flow range

- 0.4 to 4 L/min (PF2D504)
- 1.8 to 20 L/min (PF2D520)
- 4.0 to 40 L/min (PF2D540)

A single controller can monitor the flow rate of 4 different sensors.




4-channel Flow Monitor PF2D200 series

Dust generation of 3 particles/cc or less (average number)
Karman vortex eliminates moving parts and allows low dust generation.


Swept flow characteristics
Tapered side seal minimizes dead volume to reduce accumulation of liquid pool.

Particle characteristics (reference)





The data was obtained by performing an actual 10 minutes' supersonic cleaning using an average 16 M μ 2-cm of deionized water at class 10000 clean room (1 L/min flow rate).
The diameter of the measured particles ranges from 0.1 to 0.5 μ m. The flow rate used during measuring is 100 cc/min.

Swept flow characteristics (reference)



Fill the flow path with sulfuric acid and leave it for 30 minutes.
After disposing the sulfuric acid, flush the flow path out with deionized water and measure the resistance rate of the fluid that is discharged from the downstream side.
A quick recovery time indicates little liquid pool.

Processing chart for PF2D series



Vibration reducing seals
Malfunctions (output errors) that would otherwise be caused by vibration are prevented.

PFM
PFMB
PFMC
PFMV
PF2A
PF3W
LFE
PF2D
IF



For Deionized Water and Chemical Liquids

Digital Flow Switch

PF2D Series



RoHS

How to Order

Remote Type Sensor Unit

PF2D5 20 - 13 - 1 - C

Flow rate range

04	0.4 to 4 L/min
20	1.8 to 20 L/min
40	4 to 40 L/min

Port size: (inch)

11	3/8	PF2D504
13	1/2	PF2D520
19	3/4	PF2D540

Output specification

Symbol	Specification	Applicable monitor unit (monitor) model
1	Output for monitor unit + analog output (1 to 5 V)	PF2D200/300 series
2	Output for monitor unit + analog output (4 to 20 mA)	PF2D300 series

Option (Refer to page 391.)

Nil	None
C	e-con connector x 1 pc.

The cable and connector are shipped unassembled.



Specifications for Sensor Unit

Refer to pages 202 and 203 for Flow Switch Precautions. For details about the Specific Product Precautions, refer to the Operation Manual on the SMC website, <http://www.smcworld.com> Click [here](#) for details.

Model		PF2D504	PF2D520	PF2D540
Measured fluid		Liquid not to corrode nor erode deionized water and/or fluoropolymer. Viscosity: 3mPa·s (3cP) or less		
Detection style		Karman vortex		
Rated flow range		0.4 to 4 L/min	1.8 to 20 L/min ^{Note 1)}	4 to 40 L/min
Operating pressure range ^{Note 2)}		0 to 1 MPa		0 to 0.6 MPa
Proof pressure ^{Note 3)}		1.5 MPa		0.9 MPa
Operating fluid temperature		0 to 90°C		
Accuracy ^{Note 4)}		±2.5% F.S. (at 25°C water)		
Repeatability		±1% F.S. (at 25°C water)		
Temperature characteristics		±5% F.S. (0 to 50°C, based on 25°C)		
Output specifications	Pulse output	Pulse output, N channel, open drain, output for monitor unit PF2D 300/301 (Specifications: Maximum load current of 10 mA; Maximum applied voltage of 30 V)		
	Analog output	Voltage output ^{Note 5)} 1 to 5 V Accuracy: ±2% F.S., Min. load impedance: 100 kΩ (Output impedance: 1 kΩ)		
		Current output ^{Note 6)} 4 to 20 mA Accuracy: ±2% F.S. or less, Max. load impedance: 300 Ω or less with 12 VDC, 600 Ω or less with 24 VDC		
Power supply voltage		12 to 24 VDC ±10%		
Current consumption		20 mA or less (without load)		
Environmental resistance	Enclosure	IP65		
	Operating temperature range	Operating: 0 to 50°C, Stored: -25 to 85°C in stock (with no condensation and freezing)		
	Voltage resistance	1000 VAC for 1 min. between external terminals and case		
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between external terminals and case		
Standards		CE, RoHS		
Lead wire		Cabletype cord, 4 cores ø3.5, 3 m		
Weight		140 g (without lead wire)		225 g (without lead wire)
Port size		3/8 inch tube	1/2 inch tube	3/4 inch tube
Wetted material		Body: New PFA, Sensor: New PFA, Tube: Super PFA		

Note 1) 1.6 to 20 L/min (0.1 MPa) with viscosity of 1 mPa·s (1 cP) or less

Note 2) The operating pressure range drops according to the fluid temperature. See attached graph.

Note 3) 1.5 times of the maximum operating pressure and varying with fluid temperature.

Note 4) The system accuracy when combined with PF2D30C.

Note 5) When the voltage output is selected.


Note 6) When the current output is selected.

Note 7) The sensor unit conforms to the CE marking.

Note 8) For details about wiring, refer to the Operation Manual that can be downloaded from SMC website (<http://www.smcworld.com>).

Made to Order

LQ1 series fluoropolymer fittings mounting type is also available. Refer to page 392.



For Deionized Water and Chemical Liquids **PF2D Series**

Digital Flow Switch

How to Order

Remote Type
Monitor Unit

PF2D300 **0** - **A** - **M**

Output specification

0	NPN open collector 2 outputs
1	PNP open collector 2 outputs

Unit specification

Nil	With unit switching function
M	Fixed SI unit <small>(Note)</small>

(Note) Fixed units: Real-time flow rate: L/min
Accumulated flow: L

Mounting

A	Panel mounting
---	----------------



Specifications for Monitor Unit

Refer to pages 202 and 203 for Flow Switch Precautions. For details about the Specific Product Precautions, refer to the Operation Manual on the SMC website, <http://www.smcworld.com> Click [here](#) for details.

Model		PF2D300/301		
Flow rate measurement range ^{Note 1)}		0.25 to 4.5 L/min	1.3 to 21.0 L/min	2.5 to 45 L/min
Set flow rate range ^{Note 1)}		0.25 to 4.5 L/min	1.3 to 21.0 L/min	2.5 to 45 L/min
Minimum set unit ^{Note 1)}		0.05 L/min	0.1 L/min	0.5 L/min
Accumulated pulse flow rate exchange value (Pulse width: 50ms) ^{Note 1)}		0.05 L/pulse	0.1 L/pulse	0.5 L/pulse
^{Note 2)} Display units	Real-time flow rate	L/min, gal (US)/min		
	Accumulated flow	L, gal (US)		
Accumulated flow range ^{Note 1)}		0 to 999999 L		
Accuracy ^{Note 3)}		±2.5% F.S.		
Repeatability		±0.5% F.S.		
Temperature characteristics		±1% F.S. (15 to 35°C, based on 25°C) ±2% F.S. (0 to 50°C, based on 25°C)		
Current consumption (No load)		60 mA or less		
Weight		45 g		
^{Note 4)} Output specifications	Switch output	NPN open collector (PF2D300)	Maximum load current: 80 mA Internal voltage drop: 1 V or less (with load current of 80 mA) Maximum applied voltage: 30 V 2 outputs	
		PNP open collector (PF2D301)	Maximum load current: 80 mA Internal voltage drop: 1.5 V or less (with load current of 80 mA) 2 outputs	
		Accumulated pulse output	NPN open collector or PNP open collector (same as switch output)	
Environmental resistance	Enclosure	IP40		
	Operating temperature range	Operating: 0 to 50°C, Stored: -25 to 85°C (with no condensation and freezing)		
	Voltage resistance	1000 VAC for 1 min. between external terminal and case		
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between external terminal and case		
Standards		CE, RoHS		
Indicator light		3-digits 7-segment LED		
Status LED's		ON: when light is on, OUT1: Green; OUT2: Red		
Power supply voltage		12 to 24 VDC ±10%		
Response time		1sec. or less		
Hysteresis		Hysteresis mode: adjustable (can be set from 0) Window comparator mode ^{Note 5)} ; fixed (3 digits)		

Note 1 The value varies depending on set flow range

Note 2 For digital flow switch with unit switching function, (Fixed SI unit [L/min or L] will be set for switch types without the unit switching function.)

Note 3 The system accuracy when combined with PF2D5□□.

Note 4 Switch output and accumulated pulse output can be selected using the control button operation during initial setting.

	1	2	3	4
Output 1	Switch output	Switch output	Accumulated pulse output	Accumulated pulse output
Output 2	Switch output	Accumulated pulse output	Switch output	Accumulated pulse output

Note 5 Window comparator mode: Since hysteresis (H) will reach 3 digits, keep P_1 and P_2 or n_1 and n_2 apart by 7 digits more. (In case of output OUT2, n_1, 2 to be n_3, 4 and P_1, 2 to be P_3, 4.)

Note 6 The monitor unit conforms to the CE marking.

Note 7 Accumulated flow rate is reset when the power supply turns OFF.

Note 8 For details about wiring, refer to the Operation Manual that can be downloaded from SMC website (<http://www.smcworld.com>).

PFM

PFMB

PFMC

PFMV

PF2A

PF3W

LFE

PF2D


IF

How to Order



4-channel Flow Monitor Remote Type Monitor Unit

Accessory / Power supply output cable (2 m)



PF2D20

Output specification

0	NPN4 outputs
1	PNP4 outputs

Unit specification

Nil	With unit switching function
M	Fixed SI unit (Note)

Note) Fixed units:
Real-time flow rate: L/min
Accumulated flow: L

Option 2 (Refer to page 391.)

Nil	None
4C	Sensor connector (4 pc.)

Option 1 (Refer to page 391.)

Nil	None
A	Panel mounting
B	Front protective cover + Panel mounting

Connectable remote type sensor part is PF2D50□□-□-1 (with analog output 1 to 5 V).

Specifications

Refer to pages 202 and 203 for Flow Switch Precautions. For details about the Specific Product Precautions, refer to the Operation Manual on the SMC website, <http://www.smcworld.com> Click [here](#) for details.

Model		PF2D200/201		
Applicable flow rate sensor		PF2D504-□-1	PF2D520-□-1	PF2D540-□-1
Flow rate measurement range ^{Note 1)}		0.25 to 4.50 L/min	1.3 to 21.0 L/min	2.5 to 45.0 L/min
Set flow rate range ^{Note 1)}		0.25 to 4.50 L/min	1.3 to 21.0 L/min	2.5 to 45.0 L/min
Minimum set unit ^{Note 1)}		0.05 L/min	0.1 L/min	0.5 L/min
Accumulated pulse flow rate exchange value (Pulse width: 50ms) ^{Note 1)}		0.05 L/pulse	0.1 L/pulse	0.5 L/pulse
^{Note 1)} Display units	Real-time flow rate	L/min, gal (US)/min		
	Accumulated flow	L, gal (US)		
Accumulated flow range ^{Note 1)}		0 to 999999 L, 0 to 999999 gal (US)		
Power supply voltage		24 VDC ±10% (With power supply polarity protection)		
Current consumption		55 mA or less (Not including the current consumption of the sensor)		
Power supply voltage for sensor		Same as [Power supply voltage]		
Power supply current for sensor ^{Note 2)}		Max. 110 mA (However, the total current for the 4 inputs is 440 mA maximum or less.)		
Sensor input		1 to 5 VDC (Input impedance: Approx. 800K Ω)		
Output specifications ^{Note 3)}	No. of inputs	4 inputs		
	Input protection	Excess voltage protection		
	Switch output (Real-time switch output, Accumulated switch output)	NPN open collector (PF2D200)	Maximum load current: 80 mA Internal voltage drop: 1 V or less (with load current of 80 mA) Maximum applied voltage: 30 V	
		PNP open collector (PF2D201)	Maximum load current: 80 mA Internal voltage drop: 1 V or less (with load current of 80 mA)	
	Accumulated pulse output	NPN open collector or PNP open collector (same as switch output)		
	No. of outputs	4 outputs (1 output per 1 sensor input)		
	Output protection	Short circuit protection		
	Hysteresis	Hysteresis mode: Variable (can be set from 0), Window comparator mode: Fixed (3-digits)		
Response time ^{Note 4)}		1s or less		
Accuracy ^{Note 4)}		±5% F.S.		
Repeatability ^{Note 4)}		±3% F.S.		
Temperature characteristics		±2% F.S. (0 to 50°C, based on 25°C)		
Display method		For measured value display: 4-digits, 7-segment LED (Orange) For channel display: 1-digit, 7-segment LED (Red)		
Status LED's		Illuminates when output is ON OUT1: Red		
Resistance	Enclosure	IP65 for the front face only, the rest is IP40.		
	Operating temperature range	Operating: 0 to 50°C, Stored: -10 to 60°C (with no freezing and condensation)		
	Operating humidity range	Operating or Stored: 35 to 85%RH (with no condensation)		
	Standards	CE, RoHS		
Connection		Power supply / Output connection: 8P connector, Sensor connection: 4P connector (e-con)		
Material		Housing: PBT, Monitor: PET, Backside rubber: CR		
Weight		60 g (Except for any accessories that are shipped together.)		

Note 1) Fixed SI unit [L/min or L] will be set for switch types without the unit switching function. ("M" is suffixed at the end of part number.) Accumulated flow is reset when the power supply turns OFF.

Note 2) If Vcc side on sensor input connector part is short-circuited with the 0V side, the flow monitor inside will be damaged.

Note 3) Switch output and accumulated pulse output can be selected during initial setting.

Note 4) The system accuracy when combined with an applicable flow sensor.

Note 5) This product conforms to the CE marking.

Note 6) For details about wiring, refer to the Operation Manual that can be downloaded from SMC website (<http://www.smcworld.com>).

Set Flow Rate Range and Rated Flow Range

Set the flow rate within the rated flow range.

The set flow rate range is the range of flow rate that can be set on the controller.


The rated flow range is the range that satisfies the sensor's specifications (accuracy, linearity etc.).

It is possible to set a value outside off the rated flow range, however, the specification is not be guaranteed.


Sensor	Flow rate range					
	0.4L/min	1.8L/min	4L/min	10L/min	20L/min	40L/min
PF2D504	0.4L/min		4L/min			
	0.25L/min		4.5L/min			
PF2D520	1.8L/min		20L/min			
	1.3L/min		21L/min			
PF2D540	4L/min		40L/min			
	2.5L/min		45L/min			

Flow Rate Characteristics (Pressure Characteristics)


PF2D504



PF2D520




PF2D540




Construction

PF2D504/520



PF2D540



Parts list

Number	Parts	Material
1	Body	New PFA
2	Sensor	New PFA
3	Tube	Super PFA
4	Housing A	PPS
5	Housing B	PPS
6	Housing C	PPS
7	Bushing	POM
8	Cap	PPS
9	Gasket	FKM
10	O-ring	FKM
11	Thread	Stainless steel 304
12	Lead wire	PVC

PFM

PFMB

PFMC

PFMV

PF2A

PF3W

LFE


PF2D

IF

PF2D Series


Dimensions: Remote Type Sensor Unit

PF2D504-11/520-13



Model	A
PF2D504	ø9.52
PF2D520	ø12.7


PF2D540-19



Internal Circuits and Wiring Examples


-1/2

Analog voltage output
Analog current output




-1

Analog voltage output



Analog output




Cable Specifications

No. of cable wire	4
Conductor	Nominal cross-sectional area 0.15 mm ²
Insulator	Dimension Approx. 0.5 mm
Sheath	Material Oil-resistant PVC
	O.D. 3.5 mm


Dimensions: Remote Type Monitor Unit

PF2D30[†]-A

Panel mounting type



Panel fitting dimensions



Note) Decide the length of A taking into account the size of terminal you use.


* The applicable panel thickness is 1 to 3.2 mm.

Corner: R3.5 or less

Internal Circuits and Wiring Examples


-0

NPN (2 outputs)



-1

PNP (2 outputs)



PFM

PFMB

PFMC

PFMV

PF2A

PF3W

LFE


PF2D

IF



PF2D Series

Dimensions: Remote Type Monitor Unit **for Deionized Water and Chemical Liquids** (4-channel Controller)


PF2D200/201



Front protective cover + Panel mounting




Panel fitting dimensions




* Applicable panel thickness: 0.5 to 8 mm

Dimensions: Remote Type Monitor Unit for Deionized Water and Chemical Liquids (4-channel Controller)




Power supply / Output connector (8P)



Pin no.	Terminal
①	DC (+)
②	DC (-)
③	CH1_OUT1
④	N.C.
⑤	CH2_OUT1
⑥	CH3_OUT1
⑦	CH4_OUT1
⑧	N.C.

Power supply / Output connector (accessory)




Cable Specifications

No. of cable wire	8
Conductor	Nominal cross-sectional area 0.15 mm ²
Insulator	Dimension Approx. 0.5 mm
Sheath	Material Heat-resistant polyethylene
	O.D. 4.8 mm

Internal Circuits and Wiring Examples


PF2D200

NPN (4 outputs)



PF2D201

PNP (4 outputs)



Functions/PF2D

Refer to the "Operation Manual" for information on setting and operating.

Flow rate measurement selection

Real-time flow rate and accumulated flow rate can be selected. A flow rate of up to 999999 can be accumulated. The accumulated flow rate is reset when the power supply turns OFF.

Unit switching

Display	Real-time flow rate	Accumulated flow
\dot{V}_{-1}	L/min	L
\dot{V}_{-2}	GPM	gal (US)

GPM = gal (US)/min

Note) Fixed SI unit (L/min, L, m³ or m³×10) will be set for the type without the unit switching function.

Flow rate measuring unit confirmation

This function allows to confirm the accumulated flow rate when real-time flow rate is selected and to confirm the real-time flow rate when accumulated flow rate is selected.

Error correction

For PF2D300/301

LED display	Contents	Solution
E_{r1}	A current of more than 80 mA is flowing to OUT1.	Check the load and the wiring for OUT1.
E_{r2}	A current of more than 80 mA is flowing to OUT2.	Check the load and the wiring for OUT2.
E_{r4}	The set data has changed for some reason.	Perform the RESET operation, and reset all the data again.
- - -	The flow rate is over the flow rate measurement range.	Use an adjustment valve, etc. to reduce the flow rate until it is within the flow rate range.

For PF2D200/201

LED display	Contents	Solution
E_{r1}	Over current is flowing to the load of a switch output.	Shut off the power supply. After eliminating the output factor that caused the excess current, turn the power supply back on.
E_{r0}	Internal data error.	Contact SMC.
E_{r7}	Internal data error.	
E_{r10}	Internal data error.	
E_{r5}	Internal data error.	Shut off the power supply and then reset the switch.
E_{r6}	Internal data error.	
- - -	The flow rate is over the flow rate measurement range.	Use an adjustment valve, etc. to reduce the flow rate until it is within the flow rate range.

Key lock

This function prevents incorrect operations such as changing the set value accidentally.


Accumulation clearance

This is to clear the accumulated value.

Output types


Real-time switch output, accumulated switch output, or accumulated pulse output can be selected as an output type.

Real-time switch output




Note 2) Output mode is set to inverted output at the factory before shipment.

Accumulated switch output



Note 2) Output mode is set to inverted output at the factory before shipment.

Accumulated pulse output



Note 1) Refer to the specifications of monitor unit for the flow rate value per pulse.

Functions

Copy function (PF2D200, 201 only)

Information to be copied is:

- ① Flow rate range
- ② Display mode
- ③ Display unit (Only available when the unit specification is nil.)
- ④ Output method
- ⑤ Output mode
- ⑥ Flow rate value

Peak hold, Bottom hold display function

(PF2D200, 201 only)

The maximum or minimum value can be held in the case where the real-time flow rate display mode is selected during the initial setting. The hold value is reset when the power supply turns OFF or the hold is released.

Channel select function (PF2D200, 201 only)

Every pushing the Δ button, channel selection "1→2→3→4→1..." is available. The flow rate measurement of each selected channel is shown in the monitor unit.

Channel scan function (PF2D200, 201 only)


Changes displaying the channel shown every about 2 seconds and its detected flow rate.

Option

When only optional parts are required, order with the part numbers listed below.

e-con connector

Part no.	Qty.
ZS-28-CA-2	1





In addition to the connector shown above, those listed below (female contact) can be connected.

Manufacturer	Model
3M Japan Limited	37104-3101-000FL
Tyco Electronics Japan G.K.	1-1473562-4
OMRON Corp.	XN2A-1430

Panel mounting

Pin no.	Description	Note
ZS-22-E	Panel mounting adapter A, B	With mounting bracket

Part no.	Description	Note
ZS-26-B	Panel mounting adapter	With waterproof seal, mounting screw
ZS-26-C	Front protective cover + Panel mounting adapter	With waterproof seal, mounting screw



PFM

PFMB

PFMC

PFMV

PF2A

PF3W

LFE

PF2D

IF

PF2D5 Series Made to Order

Please contact SMC for detailed dimensions, specifications and lead times.



1 Fluoropolymer fittings mounting type (Space saving type)

Attached insert bushings and nuts for LQ1 series fluoropolymer fittings on double end piping.

How to Order

Refer to page 382 for details about How to Order.

PF2D504 S - 11 - - - 1S

With LQ1 fitting

Size

Model	IN side	OUT side
11	3	3
1113	3	4 (With reducer)
1311	4 (With reducer)	3
13	4 (With reducer)	4 (With reducer)

PF2D520 S - 13 - - - 1S

With LQ1 fitting

Size

Model	IN side	OUT side
13	4	4
1319	4	5 (With reducer)
1913	5 (With reducer)	4
19	5 (With reducer)	5 (With reducer)

PF2D540 S - 19 - - - 1S

With LQ1 fitting


Size

Model	IN side	OUT side
19	5	5
1925	5	6 (With reducer)
2519	6 (With reducer)	5
25	6 (With reducer)	6 (With reducer)


Dimensions

External dimensions of the body are the same as those of standard products. Refer to page 386.


LQ1 fitting size: 3




LQ1 fitting size: 4




LQ1 fitting size: 4




LQ1 fitting size: 5



LQ1 fitting size: 5



LQ1 fitting size: 6



Made to Order Related Products




How to Order Fittings for a Product with Nuts

How to order a flow sensor, PF2D5□S series, etc. nut type fittings without a nut (including insert bushings) in one place.

LQ1 E 21 - SN

Fitting type

• Nut type fittings without a nut (including insert bushings) in one place



Applicable tubing size


Class	No.	Applicable tubing size (mm)	Reducing
3	1	10 x 8	○
3	2	8 x 6	●
3	3	6 x 4	●
4	1	12 x 10	○
4	2	10 x 8	●
5	1	19 x 16	○
5	2	12 x 10	●
6	1	25 x 22	○
6	2	19 x 16	●

Class	No.	Applicable tubing size (inch)	Reducing
3	A	3/8" x 1/4"	○
3	B	1/4" x 5/32"	●
4	A	1/2" x 3/8"	○
4	B	3/8" x 1/4"	●
5	A	3/4" x 5/8"	○
5	B	1/2" x 3/8"	●
6	A	1" x 7/8"	○
6	B	3/4" x 5/8"	●

○: Basic size ●: With reducer

Note) Please select an isometric fitting with the same size as the fitting at the flow sensor.

Order example



PFM

PFMB

PFMC

PFMV

PF2A

PF3W

LFE

PF2D

IF



PF2D Series

Applicable Fluid

Compatibility checklist: Between the digital flow switch sensor material for deionized water and chemicals and the fluid selected.

Fluid	Compatibility
Acetone	○
Ammonium hydroxide Concentration 30% or less	○
Isobutyl alcohol	×
Isopropyl alcohol	○
Hydrochloric acid Concentration 38% or less	○
Ozone	×
Hydrogen peroxide Concentration 50% or less 50°C or less	○
Ethyl acetate	○
Butyl acetate	○
Nitric acid (except fuming nitric acid) Concentration 10% or less	○
Deionized water	○
Sodium hydroxide	×
Ultra deionized water	○
Toluene	○
Hydrofluoric acid Concentration 50% or less	○
Sulfuric acid (except fuming sulfuric acid) Concentration 20% or less	○
Phosphoric acid Concentration 30% or less	○

Note 1) The material and fluid compatibility check list provides reference values as a guide only.

Note 2) It is possible that some fluids are permeable depending on the type of fluid, its density and temperature. Any permeated fluid may affect the products life.

Thus, when using these fluid types, verify the fluid in advance by testing it, prior to making a decision to use it.

- Compatibility is indicated for fluid temperatures at 90°C or less.
- The product does not have an explosion proof construction. Be sure to take measures to prevent the area around the product from becoming filled with an explosive gas, when using an explosive fluid.

Table symbols ○ : Can be used
○ : Can be used under certain conditions
× : Cannot be used



PF2D Series

Specific Product Precautions

Be sure to read this before handling the products.
Refer to back page 50 for Safety Instructions.

Return of Product

Warning

If the product to be returned is contaminated or is possibly contaminated with substances that are harmful to humans, for safety reasons, please contact SMC beforehand and then employ a specialist cleaning company to decontaminate the product. After the decontamination prescribed above has been carried out, submit a Product Return Request Sheet or the Detoxification/Decontamination Certificate to SMC and await SMC's approval and further instructions before attempting to return the item.

Please refer to the International Chemical Safety Cards (ICSC) for a list of harmful substances.

If you have any further questions, please don't hesitate to contact your SMC sales representative.

PFM
PFMB
PFMC
PFMV
PF2A
PF3W
LFE
PF2D
IF