

Crimping pliers - CRIMPFOX VARIO 4S - 1108766

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping tool for ferrules up to 4 mm²

Your advantages

- ✓ Lateral conductor entry
- ✓ Proven high-quality technology
- ✓ "The original"
- ✓ Suitable for TWIN ferrules, thanks to continuous automatic adjustment
- ✓ Process reliability, thanks to pressure lock and self-adjusting die



Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 016029
GTIN	4063151016029
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	190 mm
Width (a)	72 mm
Height (c)	22 mm

General

Crimping pliers - CRIMPFOX VARIO 4S - 1108766

Technical data

General

Color	black/green
Compression	square
Type of contact	Insulated and uninsulated ferrules
Designation	Crimping position 1
Min. cross section	0.25 mm ²
Max. cross section	4 mm ²
AWG min	24
AWG max	12
Weight	401 g
Min. cross section	0.25 mm ²
Max. cross section	4 mm ²
AWG min	24
AWG max	12

Classifications

eCl@ss

eCl@ss 9.0	21043811
------------	----------

Crimping pliers - CRIMPFOX VARIO 16S - 1108767

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping pliers for ferrules up to 16 mm²

Your advantages

- ☒ Lateral conductor entry
- ☒ Proven high-quality technology
- ☒ "The original"
- ☒ Suitable for TWIN sleeves
- ☒ Unlockable pressure lock



Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 016449
GTIN	4063151016449
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	222 mm
Width (a)	76 mm
Height (c)	25 mm

General

Crimping pliers - CRIMPFOX VARIO 16S - 1108767

Technical data

General

Color	black/green
Compression	square
Type of contact	Insulated and uninsulated ferrules
Designation	Crimping position 1
Max. cross section	6 mm ²
AWG max	10
Designation	Crimping position 2
Max. cross section	10 mm ²
AWG max	8
Designation	Crimping position 3
Max. cross section	16 mm ²
AWG max	6
Weight	582 g
Min. cross section	6 mm ²
Max. cross section	16 mm ²
AWG min	10
AWG max	6

Classifications

eCl@ss

eCl@ss 9.0	21043811
------------	----------