Product data sheet Characteristics

HEPD25

Surge protection device, HEPD, 25kA, 120/240 V, 1 phase, 3 wire, SPD type 2

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 95.00 USD



Main

		77
Product	Surge protection device	i e
Range	Square D	Diffi
Device Short Name	HEPD	

Complementary

Complementary		
Surge Current	25 kA per phase	¥
Voltage Rating	120/240 V AC). . <u>.</u>
Number of Phases	1 phase	:- :- :- :- :-
Wiring Configuration	3-wire (isolated ground)	
MCOV	150 V	
Nominal Discharge Current	10 kA	
SCCR	22 kA	
Local Signalling	1 LED green normal operation	<u>a</u>
Product destination	Load center	
Input voltage	600 V L-N	
Height	3.23 in (82.04 mm)	
Width	3.72 in (94.49 mm)	<u>.</u> 2
Depth	2.10 in (53.34 mm)	2
		ئِ

Environment

Enclosure Rating NEMA	\ 4X
-----------------------	------

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI	
Discount Schedule	DE1B	
GTIN	00785901479611	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	Yes
Country of origin	MX

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Product data sheet Characteristics

HEPD25W

Surge protection device, HEPD, 25kA, 120/240 V, 1 phase, 3 wire, SPD type 2, wholesale

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 95.00 USD



Main

Product	Surge protection device	
Range	Square D	9
Device Short Name	HEPD	
Type of packing	Wholesale	

Complementary

o o mpio montary		+
Surge Current	25 kA per phase).
Voltage Rating	120/240 V AC	,
Number of Phases	1 phase	
Wiring Configuration	3-wire (isolated ground)	
MCOV	150 V	- <u>-</u>
Nominal Discharge Current	10 kA	
SCCR	22 kA	e de la companya de l
Local Signalling	1 LED green normal operation	
Product destination	Load center	9
Input voltage	600 V L-N	
Height	3.23 in (82.04 mm)	<u>.</u> 9
Width	3.72 in (94.49 mm)	
Depth	2.10 in (53.34 mm)	Ş <u>a</u>

Environment

Enclosure Rating NEMA 4X	
--------------------------	--

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901479758
Nbr. of units in pkg.	1

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX