
Inductive proximity sensors

XS range

Easy Series

Catalogue



Simply easy!™



Telemecanique

Sensors

<i>Selection guide</i>	<i>pages 2 and 3</i>
------------------------------	----------------------

Inductive proximity sensors, increased range

■ General presentation	page 4
■ References	
□ Inductive proximity sensors	page 5
□ Fixing accessories	page 5
□ Connection accessories	page 5
■ Characteristics	page 6
■ Connections	page 6
■ Setting-up precautions	page 6
■ Dimensions	page 7
■ Detection curves	page 7

Inductive proximity sensors, standard range

■ References	
□ Inductive proximity sensors	pages 8 and 9
□ Fixing accessories	page 10
□ Connection accessories	page 10
■ Characteristics	page 11
■ Connections	page 11
■ Setting-up precautions	page 12
■ Dimensions	page 12
■ Detection curves	page 13

■ Product reference index	page 14
---------------------------------	---------

Inductive proximity sensors
XS range
Basic

Cylindrical, metal				
Increased range (1)				
Flush mountable				
				
Sensing distance Sn (mm)	2.5	4	8	15
Diameter	M8	M12	M18	M30
Power supply	--- 3-wire, 12...24 V			
Function	NO or NC			
Output	PNP or NPN			
Length (mm) for pre-cabled versions	42	49	53	57
Connection	Pre-cabled (L = 2 m) (2)			
	M8 connector, 3-pin			
	M12 connector, 4-pin			
Operating temperature	-25...+70 °C			
Degree of protection	IP 65 and IP 67			
Type reference	XS108BH●●●	XS112BH●●●	XS118BH●●●	XS130BH●●●
Pages	5			

(1) Sensors with an increased range are sold individually or are available in bulk packs on request. Please contact our Customer Care Centre.
(2) Available in lengths of 3, 5 and 7 m, depending on model. Please contact our Customer Care Centre.

Standard range							
Flush mountable				Non flush mountable			
							
1.5	2	5	10	2.5	4	8	15
M8	M12	M18	M30	M8	M12	M18	M30
⎓ 3-wire, 12...24 V				⎓ 3-wire, 12...24 V			
NO or NC				NO or NC			
PNP or NPN				PNP or NPN			
42	44	53	57	42	44	53	57
●	●	●	●	●	●	●	●
●	—	—	—	●	—	—	—
●	●	●	●	●	●	●	●
-25...+70 °C				-25...+70 °C			
IP 65 and IP 67				IP 65 and IP 67			
XS108BL●●●	XS112BL●●●	XS118BL●●●	XS130BL●●●	XS208BL●●●	XS212BL●●●	XS218BL●●●	XS230BL●●●
8 and 9				8 and 9			

Inductive proximity sensors


XS range

Basic, cylindrical, increased range, flush mountable

Three-wire DC, solid-state output

XS range Basic increased range

*Rugged, compact sensors
suitable for a variety of
applications*



XS range Basic inductive proximity sensors are used to detect metal objects without physical contact.

They are flush mountable as standard and suitable for all metal environments since they ensure a maximum sensing distance, even if there is a metal background.

These sensors are rugged and compact making them suitable for a variety of applications, including:

- Material handling
- Mobile equipment
- Packing
- Machine tools
- Escalators

They are available with the following connections:

- Pre-cabled, with 2 or 5 m cable, depending on the model
- M8 or M12 connector, for easy installation and maintenance



Excellent resistance to electromagnetic interference

- > Sensors compliant with standard IEC 60947-5-2
- > Tested for use in very harsh environments, beyond standard requirements
- > Specifically, application tests conducted in an environment prone to interference, in the vicinity of variable speed drives or motors, demonstrated very good EMC immunity

3-wire technology with NO or NC, PNP or NPN output

Advantages of 3-wire technology

These sensors comprise 2 wires for the DC supply and a third wire for the output signal.

- > PNP output: switching on the positive voltage load
- > NPN output: switching on the negative voltage load
- > Protection against reverse polarity, overloads and short circuits
- > No residual current
- > Low voltage drop

Sold in lots

Depending on the model, XS range Basic sensors are sold:

- > Individually
- > In various bulk quantities for ease of unpacking and less waste (1)

(1) Please contact our Customer Care Centre.



Cost-effective sensors with no compromise on quality

Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com

Inductive proximity sensors

XS range

Basic, cylindrical, increased range, flush mountable

Three-wire DC, solid-state output



XS108BH●●L2



XS108BH●●M8



XS108BH●●M12



XS112BH●●L●



XS112BH●●M12



XS118BH●●L●



XS118BH●●M12



XS130BH●●L●



XS130BH●●M12



XSZB1●●



XZCPV●●

Sensors, 3-wire $\overline{\text{DC}}$ 12...24 V

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
2.5	NO	PNP	Pre-cabled (L = 2 m)	XS108BHPAL2	0.070
			M8 connector	XS108BHPAM8	0.030
			M12 connector	XS108BHPAM12	0.050
	NPN		Pre-cabled (L = 2 m)	XS108BHNAL2	0.070
			M8 connector	XS108BHNAM8	0.030
	N/C	PNP	Pre-cabled (L = 2 m)	XS108BHPBL2	0.070
			M8 connector	XS108BHPBM8	0.030
			M12 connector	XS108BHPBM12	0.050

Ø 12, threaded M12 x 1

4	NO	PNP	Pre-cabled (L = 2 m)	XS112BHPAL2	0.080
			Pre-cabled (L = 5 m)	XS112BHPAL5	0.150
			M12 connector	XS112BHPAM12	0.025
		NPN	Pre-cabled (L = 2 m)	XS112BHNAL2	0.080
			M12 connector	XS112BHNAM12	0.025
	N/C	PNP	Pre-cabled (L = 2 m)	XS112BHPBL2	0.080
			M12 connector	XS112BHPBM12	0.025
		NPN	Pre-cabled (L = 2 m)	XS112BHNBL2	0.080
			M12 connector	XS112BHNBM12	0.025

Ø 18, threaded M18 x 1

8	NO	PNP	Pre-cabled (L = 2 m)	XS118BHPAL2	0.105
			Pre-cabled (L = 5 m)	XS118BHPAL5	0.175
			M12 connector	XS118BHPAM12	0.035
	NPN	Pre-cabled (L = 2 m)	XS118BHNAL2	0.105	
		Pre-cabled (L = 5 m)	XS118BHNAL5	0.175	
		M12 connector	XS118BHNAM12	0.035	
	N/C	PNP	Pre-cabled (L = 2 m)	XS118BHPBL2	0.105
			M12 connector	XS118BHPBM12	0.035
		NPN	Pre-cabled (L = 2 m)	XS118BHNBL2	0.105
			M12 connector	XS118BHNBM12	0.035

Ø 30, threaded M30 x 1.5

15	NO	PNP	Pre-cabled (L = 2 m)	XS130BHPAL2	0.165
			Pre-cabled (L = 5 m)	XS130BHPAL5	0.235
			M12 connector	XS130BHPAM12	0.075
		NPN	Pre-cabled (L = 2 m)	XS130BHNAL2	0.165
			M12 connector	XS130BHNAM12	0.075
	N/C	PNP	Pre-cabled (L = 2 m)	XS130BHPBL2	0.165
			M12 connector	XS130BHPBM12	0.075
		NPN	Pre-cabled (L = 2 m)	XS130BHNBL2	0.165
			M12 connector	XS130BHNBM12	0.075

Fixing accessories

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

Connection accessories (1)

Description	Cable length m	Reference	Weight kg
Pre-wired, straight, female connectors	5	XZCPV1141L5	0.210
	10	XZCPV1141L10	0.390
M12 connectors	5	XZCPV0566L5	0.210
	10	XZCPV0566L10	0.390
M8 connectors	5	XZCPV0566L5	0.210
	10	XZCPV0566L10	0.390
3-pin, PVC cable			

(1) For other connection accessories, visit our website: www.tesensors.com

Inductive proximity sensors

XS range

Basic, cylindrical, increased range, flush mountable
Three-wire DC, solid-state output

Characteristics			
Sensor type		XS1●●BHP●L● XS1●●BHN●L●	XS1●●BHP●M● XS1●●BHN●M●
Product certifications		UL, CSA, CEC	
Connection	Pre-cabled	Cable length: 2 or 5 m, depending on model	
	Connector	M8 or M12 connector, depending on model	
Operating zone (1)	Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...6.4
	Ø 30	mm	0...12
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection		Conforming to IEC 60529 IP 65 and IP 67	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass	
	Cable	PVC (number and c.s.a. of wires: 3 x 0.14 mm ²)	
Vibration resistance		Conforming to IEC 60068-2-6 25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance		Conforming to IEC 60068-2-27 50 gn, duration 11 ms	
Output state indication		Yellow LED, on rear	Yellow LED, 2 viewing ports at 180°
Rated supply voltage		V	12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	10...36
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	Ø 8	Hz	2500
	Ø 12	Hz	950
	Ø 18	Hz	700
	Ø 30	Hz	200
Delays	First-up	ms	≤ 15
	Response	ms	≤ 0.3
	Recovery	ms	≤ 0.3

Connections			
Connector	Pre-cabled	PNP	NPN
M8	BU: Blue BN: Brown BK: Black		
M12			

For M8 connectors, NO and NC outputs on terminal 4

Setting-up precautions					
Minimum mounting distances (mm)					
Sensors		Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 8	XS108BH	e ≥ 5	e ≥ 30	e ≥ 8	—
Ø 12	XS112BH	e ≥ 8	e ≥ 50	e ≥ 12	—
Ø 18	XS118BH	e ≥ 16	e ≥ 100	e ≥ 25	—
Ø 30	XS130BH	e ≥ 30	e ≥ 180	e ≥ 30	h ≥ 2

(1) See detection curves on next page.


Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com

Inductive proximity sensors

XS range

Basic, cylindrical, increased range, flush mountable
Three-wire DC, solid-state output


Sensor dimensions XS1●●BH●●



(1) LED

		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
		a	b	a	b	a	b
Ø 8	XS108BH●●	42	33	51	34	61	40
Ø 12	XS112BH●●	49	36	—	—	61	39
Ø 18	XS118BH●●	53	41	—	—	64	43
Ø 30	XS130BH●●	57	44	—	—	68	47

Fixing clamp dimensions XSZB108, XSZBB112, XSZBB118 and XSZBB130




		a	a1	b	b1	b2	Ø
Ø 8	XSZB108	19.9	14.5	14	12.5	7.5	8
Ø 12	XSZB112	21.9	14.5	16	15.5	8.5	12
Ø 18	XSZB118	26	15.7	22.3	20.1	11.5	18
Ø 30	XSZB130	39	21.7	35.5	31	18.5	30

(1) 2 elongated holes Ø 4 x 8 mm


Detection curves

Sensors Ø 8




Standard metal target (mm): 8 x 8 x 1
Operating zone (mm): 0...2

Sensors Ø 12




Standard metal target (mm): 12 x 12 x 1
Operating zone (mm): 0...3.2

Sensors Ø 18



Standard metal target (mm): 24 x 24 x 1
Operating zone (mm): 0...6.4

Sensors Ø 30



Standard metal target (mm): 45 x 45 x 1
Operating zone (mm): 0...12

— pick-up points
- - - drop-out points (object approaching from the side)

Inductive proximity sensors

XS range, general purpose

Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output



XS108BL●●L●



XS108BL●●M8



XS108BL●●M12



XS208BL●●L●



XS208BL●●M8



XS208BL●●M12



XS112BL●●L●



XS112BL●●M12



XS212BL●●L●



XS212BL●●M12

References

Sensing distance (Sn)	Function	Output	Connection	Reference	Weight
mm					kg

Ø 8, threaded M8 x 1

Three-wire 12-24 V, flush mountable

1.5	NO	PNP	Pre-cabled (L = 2 m)	XS108BLPAL2	0.035
			Pre-cabled (L = 5 m)	XS108BLPAL5	0.105
			M8 connector	XS108BLPAM8	0.008
			M12 connector	XS108BLPAM12	0.015
		NPN	Pre-cabled (L = 2 m)	XS108BLNAL2	0.035
			M12 connector	XS108BLNAM12	0.015

Three-wire 12-24 V, non flush mountable

2.5	NO	PNP	Pre-cabled (L = 2 m)	XS208BLPAL2	0.035
			Pre-cabled (L = 5 m)	XS208BLPAL5	0.105
			M8 connector	XS208BLPAM8	0.008
			M12 connector	XS208BLPAM12	0.015
		NPN	Pre-cabled (L = 2 m)	XS208BLNAL2	0.035

Ø 12, threaded M12 x 1

Three-wire 12-24 V, flush mountable

2	NO	PNP	Pre-cabled (L = 2 m)	XS112BLPAL2	0.070
			Pre-cabled (L = 3 m)	XS112BLPAL3	0.095
			Pre-cabled (L = 5 m)	XS112BLPAL5	0.140
			M12 connector	XS112BLPAM12	0.015
		NPN	Pre-cabled (L = 2 m)	XS112BLNAL2	0.070
			M12 connector	XS112BLNAM12	0.015
	NC	PNP	Pre-cabled (L = 2 m)	XS112BLPBL2	0.070
			M12 connector	XS112BLPBM12	0.015

Three-wire 12-24 V, non flush mountable

4	NO	PNP	Pre-cabled (L = 2 m)	XS212BLPAL2	0.070
			Pre-cabled (L = 5 m)	XS212BLPAL5	0.140
			M12 connector	XS212BLPAM12	0.015
	NPN		Pre-cabled (L = 2 m)	XS212BLNAL2	0.070
			Pre-cabled (L = 7 m)	XS212BLNAL7	0.185
			M12 connector	XS212BLNAM12	0.015
	NC	PNP	Pre-cabled (L = 2 m)	XS212BLPBL2	0.070
			Pre-cabled (L = 5 m)	XS212BLPBL5	0.140
		NPN	Pre-cabled (L = 2 m)	XS212BLNBL2	0.070

Inductive proximity sensors

XS range, general purpose

Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output



XS118BL●●L●



XS118BL●●M12



XS218BL●●L●




XS218BL●●M12



XS130BL●●L●



XS130BL●●M12



XS230BL●●L●



XS230BL●●M12

References (continued)

Sensing distance (Sn)	Function	Output	Connection	Reference	Masse
mm					kg

Ø 18, threaded M18 x 1

Three-wire 12-24 V, flush mountable

5	NO	PNP	Pre-cabled (L = 2 m)	XS118BLPAL2	0.105
			Pre-cabled (L = 5 m)	XS118BLPAL5	0.175
			M12 connector	XS118BLPAM12	0.035
	NPN		Pre-cabled (L = 2 m)	XS118BLNAL2	0.105
			Pre-cabled (L = 5 m)	XS118BLNAL5	0.175
			M12 connector	XS118BLNAM12	0.035
NC	PNP		Pre-cabled (L = 2 m)	XS118BLPBL2	0.105
			M12 connector	XS118BLPBM12	0.035

Three-wire 12-24 V, non flush mountable

8	NO	PNP	Pre-cabled (L = 2 m)	XS218BLPAL2	0.105
			Pre-cabled (L = 5 m)	XS218BLPAL5	0.175
			M12 connector	XS218BLPAM12	0.035
	NPN		Pre-cabled (L = 2 m)	XS218BLNAL2	0.105
			Pre-cabled (L = 5 m)	XS218BLNAL5	0.175
			Pre-cabled (L = 7 m)	XS218BLNAL7	0.220
			M12 connector	XS218BLNAM12	0.035
	NC	PNP	Pre-cabled (L = 2 m)	XS218BLPBL2	0.105
		NPN	Pre-cabled (L = 2 m)	XS218BLNBL2	0.105

Ø 30, threaded M30 x 1.5

Three-wire 12-24 V, flush mountable

10	NO	PNP	Pre-cabled (L = 2 m)	XS130BLPAL2	0.165
			M12 connector	XS130BLPAM12	0.075
	NPN		Pre-cabled (L = 2 m)	XS130BLNAL2	0.165
			Pre-cabled (L = 3 m)	XS130BLNAL3	0.190
			M12 connector	XS130BLNAM12	0.075
NC	PNP		Pre-cabled (L = 2 m)	XS130BLPBL2	0.165
			M12 connector	XS130BLPBM12	0.075

Three-wire 12-24 V, non flush mountable

15	NO	PNP	Pre-cabled (L = 2 m)	XS230BLPAL2	0.155
			Pre-cabled (L = 5 m)	XS230BLPAL5	0.225
			M12 connector	XS230BLPAM12	0.085
	NPN		Pre-cabled (L = 2 m)	XS230BLNAL2	0.155
			Pre-cabled (L = 7 m)	XS230BLNAL7	0.225
			M12 connector	XS230BLNAM12	0.085
	NC	PNP	Pre-cabled (L = 2 m)	XS230BLPBL2	0.155

Inductive proximity sensors

XS range, general purpose

Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output

Accessories



XSZB100



XZCPV1141L

Fixing accessories (1)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

Cabling accessories (2)

Description	Length of cable	Reference	Weight kg
Pre-wired, straight, female connectors M12 connectors, 4 pins PVC cable	5	XZCPV1141L5	0.210
	10	XZCPV1141L10	0.390
Pre-wired, straight, female connectors M8 connectors, 3 pins PVC cable	5	XZCPV0566L5	0.210
	10	XZCPV0566L10	0.390

(1) See dimensions on page 7.

(2) For other connection accessories, visit our website: www.tesensors.com

Inductive proximity sensors

XS range, general purpose

Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output

Characteristics							
Sensor type			XS1●●BLP●L● XS1●●BLN●L●	XS1●●BLP●M● XS1●●BLN●M●	XS2●●BLP●L XS2●●BLN●L	XS2●●BLP●M● XS2●●BLN●M●	
Product certifications			UL, CSA, CE				
Connection	Pre-cabled		Length 2, 3 or 5 m, depending on model	–	Length 2, 5 or 7 m, depending on model	–	
	Connector		–	M8 on Ø 8 M12 on Ø 8, Ø 12, Ø 18 and Ø 30	–	M8 on Ø 8 M12 on Ø 8, Ø 12, Ø 18 and Ø 30	
Operating zone (1)	Ø 8	mm	0...1.2		0...2		
	Ø 12	mm	0...1.6		0...3.2		
	Ø 18	mm	0...4		0...6.4		
	Ø 30	mm	0...8		0...12		
Differential travel		%	1...15 of effective sensing distance (Sr)				
Degree of protection		Conforming to IEC 60529	IP 65 and IP 67				
Storage temperature		°C	- 40...+ 85				
Operating temperature		°C	- 25...+ 70				
Materials	Case		Nickel plated brass				
	Cable		PVC 3 x 0.14 mm² except Ø 8: 3 x 0.11 mm²	–	PVC 3 x 0.14 mm² except Ø 8: 3 x 0.11 mm²	–	
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)				
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms				
Output state indication			Yellow LED, on rear	Yellow LED: 2 viewing ports at 180°	Yellow LED, on rear	Yellow LED: 2 viewing ports at 180°	
Rated supply voltage		V	12...24 with protection against reverse polarity				
Voltage limits (including ripple)		V	10...36				
Switching capacity		mA	≤ 200 with overload and short-circuit protection				
Voltage drop, closed state		V	≤ 2				
Current consumption, no-load		mA	≤ 10				
Residual current, open state		mA	–				
Maximum switching frequency	Ø 8	Hz	2500		2500		
	Ø 12	Hz	2500		1200		
	Ø 18	Hz	1200		500		
	Ø 30	Hz	500		300		
Delays	First-up	ms	≤ 15		≤ 15		
	Response	Ø 8	ms	≤ 0.3		≤ 0.3	
		Ø 12	ms	≤ 0.1		≤ 0.1	
		Ø 18	ms	≤ 0.1		≤ 0.1	
		Ø 30	ms	≤ 0.1		≤ 0.2	
		Recovery	Ø 8	ms	≤ 0.3		≤ 0.3
	Ø 12		ms	≤ 0.15		≤ 0.4	
	Ø 18		ms	≤ 0.3		≤ 1	
	Ø 30		ms	≤ 1		≤ 1.4	

Wiring schemes					
Connector		Pre-cabled	PNP	NPN	
M8	M12	BU: Blue BN: Brown BK: Black			

For M8 connectors, NO and NC outputs on terminal 4

(1) Detection curves, see page 13.

Inductive proximity sensors





XS range, general purpose

Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output


Setting-up

Minimum mounting distances (mm)



Sensors		Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 8 flush mountable	XS108BL	$e \geq 3$	$e \geq 18$	$e \geq 4,5$	$d \geq 8$ $h \geq 0$
Ø 8 non flush mountable	XS208BL	$e \geq 10$	$e \geq 30$	$e \geq 7,5$	$d \geq 24$ $h \geq 5$
Ø 12 flush mountable	XS112BL	$e \geq 4$	$e \geq 24$	$e \geq 6$	$d \geq 12$ $h \geq 0$
Ø 12 non flush mountable	XS212BL	$e \geq 16$	$e \geq 48$	$e \geq 12$	$d \geq 36$ $h \geq 8$
Ø 18 flush mountable	XS118BL	$e \geq 10$	$e \geq 60$	$e \geq 15$	$d \geq 18$ $h \geq 0$
Ø 18 non flush mountable	XS218BL	$e \geq 16$	$e \geq 96$	$e \geq 24$	$d \geq 54$ $h \geq 16$
Ø 30 flush mountable	XS130BL	$e \geq 20$	$e \geq 120$	$e \geq 30$	$d \geq 30$ $h \geq 0$
Ø 30 non flush mountable	XS230BL	$e \geq 60$	$e \geq 180$	$e \geq 45$	$d \geq 90$ $h \geq 30$

Dimensions



Flush mountable in metal

Sensors		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
		a	b	a	b	a	b
Ø 8	XS108BL	42	33	50	34	61	40
Ø 12	XS112BL	44	31	—	—	55	34
Ø 18	XS118BL	53	41	—	—	64	43
Ø 30	XS130BL	57	44	—	—	68	47

Non flush mountable in metal

Sensors		Pre-cabled (mm)			M8 connector (mm)			M12 connector (mm)		
		a	b	c	a	b	c	a	b	c
Ø 8	XS208BL	42	29	4	50	32	4	61	36	4
Ø 12	XS212BL	44	26	5	—	—	—	55	29	5
Ø 18	XS218BL	53	33	8	—	—	—	64	35	8
Ø 30	XS230BL	57	32	13	—	—	—	68	34	13

Inductive proximity sensors

XS range, general purpose


Basic, cylindrical, metal, flush and non flush mountable

Three-wire DC, solid-state output

Detection curves

Ø 8 sensors


Flush mountable in metal



Standard steel target (mm): 8 x 8 x 1

Operating zone (mm): 0...1.2

Non flush mountable in metal




Standard steel target (mm): 8 x 8 x 1

Operating zone (mm): 0...2

Ø 12 sensors


Flush mountable in metal



Standard steel target (mm): 12 x 12 x 1

Operating zone (mm): 0...1.6

Non flush mountable in metal




Standard steel target (mm): 12 x 12 x 1

Operating zone (mm): 0...3.2

Ø 18 sensors


Flush mountable in metal



Standard steel target (mm): 18 x 18 x 1

Operating zone (mm): 0...4

Non flush mountable in metal




Standard steel target (mm): 24 x 24 x 1

Operating zone (mm): 0...6.4

Ø 30 sensors


Flush mountable in metal



Standard steel target (mm): 30 x 30 x 1

Operating zone (mm): 0...8

Non flush mountable in metal



Standard steel target (mm): 45 x 45 x 1

Operating zone (mm): 0...12

— pick-up points
- - - drop-out points (object approaching from the side)

Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com

X		XS130BLPBL2	9
XS108BHNAL2	5	XS130BLPBM12	9
XS108BHNAM8	5	XS208BLNAL2	8
XS108BHPAL2	5	XS208BLPAL2	8
XS108BHPAM8	5	XS208BLPAL5	8
XS108BHPAM12	5	XS208BLPAM8	8
XS108BHPBL2	5	XS208BLPAM12	8
XS108BHPBM8	5	XS212BLNAL2	8
XS108BHPBM12	5	XS212BLNAL7	8
XS108BLNAL2	8	XS212BLNAM12	8
XS108BLNAM12	8	XS212BLNBL2	8
XS108BLPAL2	8	XS212BLPAL2	8
XS108BLPAL5	8	XS212BLPAL5	8
XS108BLPAM8	8	XS212BLPAM12	8
XS108BLPAM12	8	XS212BLPBL2	8
XS112BHNAL2	5	XS212BLPBL5	8
XS112BHNAM12	5	XS218BLNAL2	9
XS112BHNBL2	5	XS218BLNAL5	9
XS112BHNB12	5	XS218BLNAL7	9
XS112BHPAL2	5	XS218BLNAM12	9
XS112BHPAL5	5	XS218BLNBL2	9
XS112BHPAM12	5	XS218BLPAL2	9
XS112BHPBL2	5	XS218BLPAL5	9
XS112BHPBM12	5	XS218BLPAM12	9
XS112BLNAL2	8	XS218BLPBL2	9
XS112BLNAM12	8	XS230BLNAL2	9
XS112BLPAL2	8	XS230BLNAL7	9
XS112BLPAL3	8	XS230BLNAM12	9
XS112BLPAL5	8	XS230BLPAL2	9
XS112BLPAM12	8	XS230BLPAL5	9
XS112BLPBL2	8	XS230BLPAM12	9
XS112BLPBM12	8	XS230BLPBL2	9
XS118BHNAL2	5	XSZB108	5
XS118BHNAL5	5		10
XS118BHNAM12	5	XSZB112	5
XS118BHNBL2	5		10
XS118BHNB12	5	XSZB118	5
XS118BHPAL2	5		10
XS118BHPAL5	5	XSZB130	5
XS118BHPAM12	5		10
XS118BHPBL2	5	XZCPV0566L5	5
XS118BHPBM12	5		10
XS118BLNAL2	9	XZCPV0566L10	5
XS118BLNAL5	9		10
XS118BLNAM12	9	XZCPV1141L5	5
XS118BLPAL2	9		10
XS118BLPAL5	9	XZCPV1141L10	5
XS118BLPAM12	9		10
XS118BLPBL2	9		
XS118BLPBM12	9		
XS130BHNAL2	5		
XS130BHNAM12	5		
XS130BHNBL2	5		
XS130BHNB12	5		
XS130BHPAL2	5		
XS130BHPAL5	5		
XS130BHPAM12	5		
XS130BHPBL2	5		
XS130BHPBM12	5		
XS130BLNAL2	9		
XS130BLNAL3	9		
XS130BLNAM12	9		
XS130BLPAL2	9		
XS130BLPAM12	9		

Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

www.tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

April 2022 - V3.0