

Industrial Display Solutions

Leading Industrial Display Expert

- ✓ Leading Technology and Capability
- ✓ Product Offerings
- ✓ Design To Order Services
- ✓ Market Solutions
- ✓ Product Selection



ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com

Advantech In-house Design Capabilities

Leading Professional Display Expert

Advantech designs, develops, and manufactures display systems that meet the demands of various global system integration markets. These include gaming, automation, kiosk, and medical markets. By combining proven technologies and flexible manufacturing, Advantech creates class leading solutions that deliver significant product differentiation and competitive advantages. Our customer-centric approach reinforces all of our activities and is an essential part of the thousands of products we ship daily.



Touchscreen
Integration



Optical
Bonding



High
Brightness



Curved
Display



Pioneering Industrial Display Technologies

Advantech is dedicated to developing industry-leading display technologies. We are a pioneer in optical enhancement solutions including high brightness optical bonding, curved play solutions, panel resizing, and wide temperature solutions.

Capabilities for Display solution



DeviceOn/Display



Global In-house Design and Manufacturing Capabilities

Advantech has built in-house class 1,000/10,000 LCD clean rooms in Taiwan, China, and North America with a monthly capacity of 30,000 units. We offer reliable high-quality industrial display products.




15+ Years of Supplying the Global Industrial Displays Market

Advantech's Industrial Display Solutions team has 15 years of experience building high quality leading edge industrial display products and is dedicated to helping customers adopt the latest technology.

Leading Technologies

OPTICAL BONDING

Optical bonding technology removes air gaps by injecting optical glue into the space between a cover glass and the LCD panel. This reduces sunlight reflections to improve image quality. Advantech develops both Wet Bond (OCR) and Dry Bond (OCA) technologies with high vibration and impact resistance to enhance LCD readability and durability.




Before

Ambient sunlight causes image washout



After

Sunlight reading issue



HIGH BRIGHTNESS

Using a built-in LED light bar, optical films, and high-efficiency thermal technology, Advantech's solution can boost brightness up to 2000nits. The lowpower backlight source uses 20% less energy than competing products with the same level of brightness. Advantech also offers an excellent automatic dimming solution which can save up to 50% on power consumption.



MEDICAL IMAGING

Advantech's solutions include IPS displays and AD boards with color management functionality to help improve brightness stability, gray scale, color temperature, and color gamut to ensure uniformity. Our solution is fully compliant with the DICOM part 14 standards. It also incorporates WiseAgent, a Network Remote Diagnostics Tool for remote control and monitoring.



CURVED DISPLAY

Advantech curved display technology is available with concave or convex surfaces including 1500R or 1200R. Packaged together with an industrial grade video card and power supply, our solution is available with standard video inputs and can be specified with or without a 10-point touch overlay. Advantech also provides open frame monitors and panel module products to support different application needs.





WIDE TEMPERATURE

Advantech Thermal Impedance Solution uses a heating film and a built-in intelligent AD board for auto on/off control. This allows the LCD display to raise the temperature to accommodate different working environments. It can also turn the heating film/glass on or off automatically to save energy.

INDEPENDENT 6-AXIS COLOR ADJUSTMENT

The six-axis adjustment feature allows independent adjustments of six different colors (red, green, blue, cyan, magenta, and yellow), providing a higher degree of color adjustment flexibility.



Industrial Touch LCD Kit

Turnkey kits for Advantech SBC

The Advantech industrial LCD Kit series provides industrial grade touch LCD panels integrated with resistive touch screens, projective touch screens, and compatible AD board kit solutions. Advantech's LCD kit series is fully compatible with all Advantech's embedded boards and features LVDS and backlight cables options, ready VBIOS, and touch driver support.



Series Feature Highlight

EMI Shielding



Improve Signal Clarity

Shield extraneous electromagnetic and radio frequency signals that disrupt device performance



Increase Data Integrity

Prevent external signals from interfering from critical data streams

High Brightness



Superior brightness of
1000~1800nits



Low power consumption

IDK-1000 Indoor LCD Kit



Four circular icons representing features of the IDK-1000 Indoor LCD Kit:

- DICOM model available
- 5.7"~21.5"
- LVDS interface
- Resistive/PCAP touchscreen



IDK-2000 Outdoor LCD Kit



Four circular icons representing features of the IDK-2000 Outdoor LCD Kit:

- Sunlight readable
- 7"~21.5"
- LVDS interface
- PCAP touch




Industrial Touch Monitor

Advantech provides comprehensive monitor solutions with different front frame chassis options. Customers can make choices based on their integration needs. All of Advantech's industrial grade monitors feature slim and light designs for easy and efficient installation.



Series Feature Highlight

Flexible Mechanical design



Open frame



Panel mount

Versatile Touch solution



Resistive touch



P-cap touch



Tempered glass

IDS-3100 Open Frame Monitors



6.5"~27"

Wide temperature

Resistive/PCAP touchscreen

VESA mount
75 x 75 &
100 x 100 mm



IDS-3200 Panel Mount Monitors



6.5"~21.5"

Resistive/PCAP touchscreen

VESA mount
75 x 75 &
100 x 100 mm

Rugged front frame



Industrial Full-flat Monitors

Advantech provides 100% flat glass front touch monitors suitable for myriad applications including medical and point-of-sale/information solutions. These flat monitors' feature a metal chassis which enables easy cleaning and maintenance, and provides a rugged and stable platform for diverse applications.



Series Feature Highlight

Compact design



Slim and light weight



Panel mount integration

Ruggedize design




Front frame IP65



Wide temp support -20~70°C

IP65 water and dust proof designs can eliminate downtime in harsh environments by preventing the ingress of particulates and moisture/water. The IP65 rated industrial grade monitor can enable access to production equipment and machines without issues caused by dust and water. An IP rating is defined by two numbers: the first number represents protection from solid objects or materials, and the second represents protection from liquids.



IDP31 Proflat Monitors





100% flat, IP-rated front screen



7"~23.8"



Multi-touch



Bezel-less design



Audio solution



VGA/DVI/HDMI interface



Digital Signage Solutions

Advantech provides a standalone plug-and-play display for digital signage solutions. This signage display enables professional-grade image quality with optional interactive touch. It supports resolutions ranging from Full HD to 4K UHD. To fulfill the multiple connection requests of signage systems, it supports signal interfaces for HDMI, Display Port, and SDM interface.



Series Feature Highlight

Robust design



Fan-less thermal management



24/7 operation

User friendly



Multiple signal interface



VESA mounting support

DSD-3000 Signage Monitors



- 32"~55"
- Wide ratio of 16:9
- High resolution
- Portrait/landscape mode
- Multiple signal interface

DSD-5000 Stretched Monitors



- 28" & 38"
- Super wide ratio of 16:3
- RS232 remote control
- Multiple I/O
- Audio solution

Gaming Display Solutions

This range of shaped monitors heralds the arrival of bold and daring designs for industrial displays. Available in C or J styles, the curved display series is built with a durable industrial grade standard. They use long life parts and tempered vandal proof glass. The fully flush finish makes the units easier to clean.



Series Feature Highlight

Immersive design



Curved shape of 1500 radius



LED strip integrated

Superior viewing performance




High color gamut



Wide view angle

IDP31 Proflat Monitors with LED Strip Lights



23.8", 27"


Multi-touch

LED lighting surrounding

Bezel-less design

VGA/DVI/DP interface

CRV C/J type Curved Touch Monitors



High resolution UHD


PBP/PIP support

Multi-touch

Thermal solution

Wide viewing angle

CRV C/J type Curved Touch Monitors with LED Strip Lights



LED Strip Lights surrounding

Multi-touch

1500R radius curve

PIP Function

High resolution UHD

Smart Parking

The contactless payment transactions become popular. Parking payment solutions that helps end users to do the transactions by themselves .

The off-street parking systems will need to deliver clear information and provides reliable usage.



Solution:

Advantech's IDK-1110WP, a 10.1 inch touch panel kit with 1000nits ultra high brightness, which could deliver the excellent visibility performance even during the direct sunlight. The touch panel kit is Integrated with projected capacitive touch solution by optical bonding solution that supports operation with quick response, and could avoid the sunlight reflection under sunlight.

Solution Highlights:

- IDK-1110W series
- High brightness
- Projected capacitive touch
- Optical bonding

Gaming

The Slot machine with curved touch monitors could enhance the attraction through the stylish curved shape design, with the integrated LED lighting strips surrounding the display also brings attraction when winning the game.



Solution:

Advantech's CRV-430WP which is a 43" curved touch monitor with LED strip, also equipped with a LED controller for versatile LED color configuration, which could enhance the immersive and impressed viewing experience of the slot machine. The touch monitor mechanically represents the C shape design that helps to provide the best viewing performance when the player sits in front of the Slot machine.

Solution Highlights:

- CRV-430WP series
- High resolution of 3840 x 2160
- Projected capacitive touch
- Radius of 1500 design

Medical Testing Equipment

Molecular Diagnostics platform builder which is used for PCR inspection. The platforms are sample-to-answer, real-time PCR systems crafted to increase laboratory efficiency, ensure result accuracy, and fit seamlessly into today's lean laboratory.



Solution:

Advantech's IDK-1115WP, a 15.6 inch wide ratio panel with 450nits brightness which could deliver excellent display performance. The panel is Integrated with P-cap touch solution that supports gloved operation in laboratory. Meanwhile, the projective touch is with surface treatment of anti-finger print that helps to minimize the finger print when doing the operation.

Solution Highlights:

- IDK-1115W series
- High resolution of 1920 x 1080
- Projected capacitive touch
- Wide viewing angle

Factory Automation

Automatic Optical inspection (AOI) solutions have in the meantime been developed to such a reliable level that manual inspection can be completely replaced. With the information collected through AOI systems, yields can be increased. The machine apply with a touch monitor that could provide stable operation with precise action.



Solution:

Advantech's IDS-3215, a 15 inch touch panel mount monitor with multiple signal interfaces and USB interface for touch function. The comprehensive design that helps customer easy integration, flexible signal connection, and stable reliability. The monitor is equipped with 5 wires resistive touch that could support 10 millions operation touch without worry, the display supports 1024 x 768 resolution with brightness 500nits that helps to deliver clear instruction for operation.

Solution Highlights:

- IDS-3215 series
- Panel mount integration
- Resistive touch
- Backlight lifetime 70,000 hrs

Design-to-order Services

Advantech provides DTOS service to design and manufacture displays tailored to your unique demands. Our design teams are located close to our customers in order to efficiently translate OEM requirements into cost effective, cleverly engineered solutions for all manner of environments.

Industrial Display DTOS Services

Full Customization, Tailor-made



Key Applications

Our teams develop hundreds of new designs each year and are veterans of many demanding applications such as:



Medical Testing

- Expansive Viewing
- Excellent Noise Immunity
- Anti-fingerprint Coating



Automation

- PCAP touch supports multi touch
- IP65 front panel
- Panel mount integration



Kiosk

- Bezel-less design
- Versatile signal DVI/HDMI
- Open frame integration



Gaming

- High resolution FHD/UHD
- P-cap touch for multi touch
- Curved display

DeviceOn/Display

Advantech's DeviceOn/Display software utility delivers remote monitoring, status visualization, and real-time management to individual display devices. DeviceOn/Display can support display function adjustment via central control or handheld devices. The operating status can be monitored with problems recorded on a server daily. This solution eases management control and saves time.

Functions Highlights



On Screen Display Control

- Brightness adjustment
- Color temperature



Touch Function Settings

- Touch function enable/disable
- Remote touch calibration
- Remote touch debug



Remote Monitoring

- Backlight lifetime monitoring




Remote Task Management

- Grouping settings
- Power-on timer settings

Advantages of using Advantech DeviceOn/Display

DeviceOn/Display is the cutting-edge remote display management software that boosts display performance, enables customization, and reduces workplace hazards.



Selection Guide



IDK-1000 Indoor LCD Kits

	IDK-1105	IDK-1106	IDK-1107W		IDK-1110W		IDK-1110	
Size	5.7"	6.5"	7"		10.1"		10.4"	
Resolution	640 x 480, VGA	640 x 480, VGA	800 x 480, WVGA	1024 x 600, WVGA	1024 x 600, WSVGA	1280 x 800, WXGA	800 x 600, SVGA	1024 x 768, XGA
Brightness (cd/m ²)	500	800	500	500	500	500	400	500
Viewing Angle (H/V°)	140/100	160/140	178/178	178/178	140/120	170/170	160/130	176/176
Contrast Ratio	250:1	600:1	800:1	800:1	500:1	800:1	700:1	1000:1
Touchscreen	4-Wire Resistive	4-Wire Resistive	5-Wire Resistive and P-cap	P-cap	4-Wire Resistive	P-cap	4-Wire Resistive	4-Wire Resistive and P-cap
Signal Interface	LVDS	LVDS	LVDS	LVDS	LVDS	LVDS	LVDS	LVDS
Backlight Life (hrs)	30,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000
Durability (touches)	1 million	1 million	1 million	No limit	1 million	No limit	1 million	1 million
Operating Temperature	-20 ~ 70°C	-10 ~ 60°C	-5 ~ 60°C	-20 ~ 70°C	-5 ~ 60°C	-20 ~ 65°C	-10 ~ 60°C	-10 ~ 60°C

	IDK-1112	IDK-1115	IDK-1115WP	IDK-1121W	
Size	12.1"	15"	15.6"	21.5"	
Resolution	1024 x 768, XGA	1024 x 768, XGA	1920 x 1080, FHD	1920 x 1080, FHD	1920 x 1080, FHD
Brightness (cd/m ²)	500	500	450	300	250
Viewing Angle (H/V°)	178/178	178/178	170/170	178/178	178/178
Contrast Ratio	1000:1	2500:1	800:1	5000:1	1000:1
Touchscreen	5-Wire Resistive and P-cap	5-Wire Resistive and P-cap	P-cap	5-Wire Resistive	P-cap
Signal Interface	LVDS	LVDS	2 Channel LVDS	2 Channel LVDS	2 Channel LVDS
Backlight Life (hrs)	30,000	70,000	50,000	50,000	30,000
Durability (touches)	10 / No limit	10 / No limit	No limit	10 million	No limit
Operating Temperature	-20 ~ 70°C	-20 ~ 70°C	-20 ~ 70°C	0 ~ 60°C	0 ~ 50°C



IDK-2000 Outdoor LCD Kits

	IDK-2107	IDK-2108	IDK-2110W	IDK-2110		IDK-2115	IDK-2115W	IDK-2121W
Size	7"	8.4"	10.1"	10.4"		15"	15.6"	21.5"
Resolution	1024x600 WSVGA	800 x 600 SVGA	1280x800 WXGA	800 x 600 SVGA	1024 x 768 XGA	1024 x 768 XGA	1920 x 1080 FHD	1920 x 1080 FHD
Brightness (cd/m ²)	1000	1200	1500	1200	1000	1200	1200	1200
Viewing Angle (H/V°)	170/170	160/140	170/170	160/130	176/176	178/178	170/170	178/178
Contrast Ratio	800:1	600:1	800:1	500:1	1000:1	2500:1	800:1	5000:1
Touchscreen	P-CAP	4-Wire Resistive	P-CAP	4-Wire Resistive	P-CAP	5-Wire Resistive	PCAP	P-CAP
Signal Interface	LVDS	LVDS	LVDS	LVDS	LVDS	LVDS	2 Channel LVDS	2 Channel LVDS
Backlight Life (hrs)	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000
Durability (touches)	No limit	1 million	No limit	1 million	No limit	10 million	No limit	No limit
Operating Temperature	-20 ~ 70°C	-20 ~ 70°C	-20 ~ 70°C	-10 ~ 60°C	-20 ~ 70°C	-20 ~ 70°C	0 ~ 55°C	0 ~ 60°C



IDS-3100/3200 Slim Open Frame/Panel Mount Monitors

	IDS-3106/ IDS-3206	IDS-3110/ IDS-3210	IDS-3112/ IDS-3212	IDS-3115/ IDS-3215	IDS-3117/ IDS-3217	IDS-3118W/ IDS-3218W	IDS-3119/ IDS-3219	IDS-3121W/ IDS-3221W	IDS-3127W
Size	6.5"	10.4"	12.1"	15"	17"	18.5"	19"	21.5"	27"
Resolution	640 x 480, VGA	800 x 600, SVGA 1024 x 768, XGA	800 x 600, SVGA 1024 x 768, XGA	1024 x 768, XGA	1280 x 1024, SXGA	1366 x 768, HD	1280 x 1024, SXGA	1920 x 1080, FHD	1920 x 1080, FHD
Brightness(cd/m²)	800	400/500	450/600	400/500	350	300	350	250	300
Viewing Angle(H/V°)	160/140	160/140	160/140	160/140	170/160	170/160	170/160	178/178	178/178
Contrast Ratio	600 : 1	700 : 1	700 : 1	700 : 1	800 : 1	1000:1	1000:1	1000:1	3000:1
Touchscreen	Glass and 4-Wire Resistive	5-wire Resistive and P-cap	5-wire Resistive and P-cap	5-wire Resistive and P-cap	Glass and 5-Wire Resistive	5-wire Resistive and P-cap	Glass and 5-wire Resistive	5-wire resistive and P-cap	Glass and p-cap
Backlight Life (hrs)	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000	30,000
Durability	1 million touches	10/50 million touches	10/50 million touches	10/50 million touches	10 million touches	10/50 million touches	10/50 million touches	10/50 million touches	50 million touches
Operating Temperature	0 ~ 50°C	- 20 ~ 60°C	- 20 ~ 60°C	- 20 ~ 60°C	- 20 ~ 60°C	0 ~ 55°C	0 ~ 45°C	0 ~ 45°C	0 ~ 45°C
I/O Ports	VGA x 1; DVI x 1; 12 VDC Jack x 1; USB x 1	VGA x 1; DVI x 1; HDMI x 1 (selected models); 12 VDC Jack x 1; USB x 1; RS-232 x 1							VGA x 1; DVI x 1; DP x 1; 12 VDC Jack x 1; USB x 1
OSD	Keys: Power on/off, Menu/Enter, Left/Up, Right/Down, Exit/Auto, Source Menu Functions: Brightness, Contrast, Screen Setting, Color Temp, OSD Language, VGA/DVI, Reset, Auto Adjust								



IDS-3300 Industrial IP65 Monitors

	IDS-3315	IDS-3319
Size	15"	19"
Resolution	1024 x 768, XGA	1280 x 1024, SXGA
Brightness (cd/m ²)	500 / 1200	350
Viewing Angle (H/V°)	176/176	170/160
Contrast Ratio	2500:1	1000:1
Touchscreen	5-Wire Resistive Touchscreen / Projected Capacitive Touchscreen	5-Wire Resistive Touchscreen / Projected Capacitive Touchscreen
Backlight Life (hrs)	70,000/50,000	50,000
Durability	10 million touches	10 million touches
Operating Temperature	- 20 ~ 60°C	-20 ~ 60° C
I/O Ports	VGA x 1; DVI x 1; HDMI x 1 12VDC Jack x 1; USB x 1; RS-232 x 1	
OSD	Keys: Power on/off, Menu/Enter, Left/Up, Right/Down, Exit/Auto, Source Menu Functions: Brightness, Contrast, Screen Setting, Color Temp, OSD Language, VGA/DVI, Reset, Auto Adjust	

Selection Guide

IDP31 Series Proflat Touch Monitors



	IDP31-101WP	IDP31-150	IDP31-150P	IDP31-156W	IDP31-156WP	IDP31-215W	IDP31-215WP
Size	10.1"	15"	15"	15.6"	15.6"	21.5"	21.5"
Resolution	1280 x 800, WXGA	1024 x 768, XGA	1024 x 768, XGA	1920 x 1080, FHD	1920 x 1080, FHD	1920 x 1080, FHD	1920 x 1080, FHD
Brightness(cd/m²)	500/1200	500	500/1200	450	450/1200	250	250/1200
Viewing Angle (H/V°)	170/170	178/178	178/178	170/170	178/178	178/178	178/178
Contrast Ratio	800:1	1500:1	1000:1	800:1	800:1	1000:1	1000:1
Touchscreen	Projective Capacitive Touch	Projective Capacitive Touch	Projective Capacitive Touch	Projective Capacitive Touch	Projective Capacitive Touch	Projective Capacitive Touch	Projective Capacitive Touch
I/O Ports	HDMI 12 VDC Jack x 1; USB x 1	HDMI x 1; VGA x 1; DVI-D x 1 Audio x 1 (audio output 3W) 12 VDC Jack x 1; USB x 1	HDMI 12 VDC Jack x 1; USB x 1	HDMI x 1; VGA x 1; DVI-D x 1 Audio x 1 (audio output 3W) 12 VDC Jack x 1; USB x 1	HDMI 12 VDC Jack x 1; USB x 1	HDMI x 1; VGA x 1; DVI-D x 1 Audio x 1 (audio output 3W) 12 VDC Jack x 1; USB x 1	HDMI 12 VDC Jack x 1; USB x 1
Surface Hardness	7H	6H	6H	6H	7H	7H	7H
Backlight Life (hrs)	50,000	50,000	50,000	50,000	50,000	30,000	50,000
Operating Temperature	-20 ~ 65 °C	-20 ~ 60 °C	-20 ~ 70 °C	-20 ~ 60 °C	-20 ~ 65 °C	0 ~ 45°C	-20 ~ 60 °C
Certification	CE, FCC, CCC	CE, FCC, CCC	CE, FCC, CCC	CE, FCC, CCC	CE, FCC, CCC	CE, FCC, CCC	CE, FCC, CCC

IDP31 with LED



	IDP31-238W	IDP31-270W
Size	23.8"	27"
Resolution	1920 x 1080	1920 x 1080
Brightness(cd/m²)	350	300
Viewing Angle (H/V°)	178/178	178/178
Contrast Ratio	1000:1	3000:1
Touchscreen	Glass and P-cap	Glass and P-cap
I/O Ports	VGA x 1; DVI x 1; DP x 1; 12 VDC Jack x 1; USB x 1	VGA x 1; DVI x 1; DP x 1; 12 VDC Jack x 1; USB x 1
Surface Hardness	6H	6H/7H
Backlight Life (hrs)	30,000	30,000
Operating Temperature	0 ~ 45° C	0 ~ 45° C
Certification	CE, FCC, CCC	CE, FCC, CCC

DSD-3000 Large Format Digital Signage Displays



	DSD-3032	DSD-3043	DSD-3055
Size	32"	43"	55"
Resolution	1920 x 1080(FHD)	1920 x 1080(FHD)	3840 x 2160(UHD)
Brightness (cd/m²)	350	500	500
Viewing Angle (H/V°)	178/178	178/178	178/178
Contrast Ratio	3000:1	4000:1	4000:1
Touchscreen	Optical Touch	Optical Touch	Optical Touch
Signal Interface	HDMI/VGA/ DisplayPort	HDMI/VGA/ DisplayPort	HDMI/VGA/ DisplayPort
Backlight Life (hrs)	50,000	50,000	50,000
Durability	10 million touches	10 million touches	10 million touches
Operating Temperature	5 ~ 45° C	5 ~ 45° C	5 ~ 45° C

DSD-5000 Stretched Digital Signage Displays



	DSD-5028	DSD-5038
Size	28"	38"
Resolution	1920 x 360	1920 x 538
Brightness (cd/m ²)	700	800
Viewing Angle (H/V°)	178/178	176/176
Contrast Ratio	1200:1	4000:1
Touchscreen	N/A	N/A
Signal Interface	VGA/DVI/HDMI	VGA/DVI/HDMI
Backlight Life (hrs)	50,000	50,000
Durability	N/A	N/A
Operating Temperature	0 ~ 45° C	0 ~ 45° C

CRV Curved Multi-touch Displays



	CRV-430WP	CRV-430JP
Size	43" C type	43" J type
Resolution	3840 x 2160 UHD	
Brightness (cd/m ²)	450	
Contrast Ratio	1100:1 (8ms)	
Curved Radius	1500	
Touchscreen	Multi-touch PCT(10 touches)	
Cover Glass	4mm	
Operating Temperature	0 ~ 50° C	
I/O Ports	HDMI 1.4 (2 ports), HDMI 2.0 (1 ports), DisplayPort, VGA,	

CRV Curved Multi-touch Displays with LED



	CRV-430WP	CRV-430JP
Size	43" C type	43" J type
Resolution	3840 x 2160 UHD	
Brightness (cd/m ²)	450	
Contrast Ratio	1100:1 (8ms)	
Curved Radius	1500	
Touchscreen	Multi-touch PCT(10 touches)	
Cover Glass	4mm	
Operating Temperature	0 ~ 50° C	
I/O Ports	HDMI 1.4 (2 ports), HDMI 2.0 (1 ports), DisplayPort, VGA,	

Your Industrial Displays Expert



Industrial Grade and Quality

Advantech provides display solutions for industrial applications requiring greater durability and quality.



Extended Longevity and Warranty

Advantech offers a 2 year product warranty. An extended warranty between 3 years is also available.



Global Capacity and Local Service

Advantech delivers display solutions globally with three manufacturing centers in Taiwan, China, Netherlands, and USA as well as branch offices in 23 countries.

Regional Service and Customization Centers

China | Kunshan
86-512-5777-5666

Taiwan | Taipei
886-2-2792-7818

Netherlands | Eindhoven
31-40-267-7000

Poland | Warsaw
00800-2426-8080

USA | Milpitas, CA
1-408-519-3898

Worldwide Offices

Asia Pacific

Taiwan
Toll-Free 0800-777-111
Taipei & IoT Campus 886-2-2792-7818
Taichung 886-4-2372-5058
Kaohsiung 886-7-392-3600

China
Toll-Free 800-810-0345
Beijing 86-10-6298-4346
Shanghai 86-21-3632-1616
Shenzhen 86-755-8212-4222
Chengdu 86-28-8545-0198
Hong Kong 852-2720-5118

Middle East and Africa

Israel 072-2410527
Turkey 90-212-222-0422
Turkey-Bursa 90-224-413-3134

Asia Pacific

Japan
Toll-Free 0800-500-1055
Tokyo 81-3-6802-1021
Osaka 81-6-6267-1887
Nagoya 81-0800-500-1055
Nogata 81-949-22-2890

Korea
Toll-Free 080-363-9494/5
Seoul 82-2-3660-9255

Singapore
Singapore 65-6442-1000

Malaysia
Kuala Lumpur 60-3-7725-4188
Penang 60-4-537-9188

Thailand
Bangkok 66-02-2488306-9

Vietnam
Hanoi 84-24-3399-1155
Hochiminh 84-28-3836-5856

Indonesia
Jakarta 62-21-751-1939

Australia
Toll-Free 1300-308-531
Melbourne 61-3-9797-0100

India
Bangalore 91-94-4839-7300
Pune 91-94-2260-2349

Europe

Netherlands
Eindhoven 31-40-267-7000
Breda 31-76-523-3100

Germany
Toll-Free 00800-2426-8080/81
Munich 49-89-12599-0
Düsseldorf 49-2103-97-855-0

France
Paris 33-1-4119-4666

Italy
Milan 39-02-9544-961

UK
Newcastle 44-0-191-262-4844
London 44-0-870-493-1433

Spain
Madrid 34-91-668-86-76

Sweden
Stockholm 46-0-864-60-500

Poland
Warsaw 48-22-31-51-100

Russia
Moscow 8-800-555-01-50
St. Petersburg 8-812-332-57-27
8-921-575-13-59

Czech Republic
Ústí nad Orlicí 420-465-524-421

Ireland
Galway 353-91-792444

Americas

North America
Toll-Free 1-888-576-9668
Cincinnati 1-513-742-8895
Milpitas 1-408-519-3898
Irvine 1-949-420-2500
Ottawa 1-815-433-5100
Chicago 1-888-576-9668

Brazil
Toll-Free 0800-770-5355
São Paulo 55-11-5592-5367

Mexico
Toll-Free 1-800-467-2415
Mexico City 52-55-6275-2777

ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Please verify specifications before ordering. This guide is intended for reference purposes only. All product specifications are subject to change without notice. No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher. All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2023

View online



8600000641

Courtesy of Steven Engineering, Inc - (800) 258-9200 - sales@steveneng.com - www.stevenengineering.com