TX-RX CROSS-REFERENCE

FIBER MEDIA CONVERSION PRODUCTS
DESIGNED FOR ONE-WAY, SECURE DATA APPLICATIONS



COMMON FEATURES

- Plug-and-play, driver-free installation
- Built-in Auto Negotiation and Auto Cross functions

One-Way Data Traffic Media Converters								
Note: Images are representations and may vary according to model/part number.	Wines Committee of the		West, San		Marion of the state of the stat			
Product Family	Giga-MiniMc		MiniMc		McLIM		McPC Giga-MediaLinX Low-Profile PCI	
Port Configurations	1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber		1 Copper / 1 SC Fiber	
Features	Auto-Cross, Auto-Negotiation		Auto-Cross, Auto-Negotiation		Auto-Cross, Auto-Negotiation, LinkLoss, FiberAlert		Auto-Cross, Auto-Negotiation	
Device Speed	10/100/1000 Mbps Copper to 1000 Mbps Fiber		10/100 Mbps Copper to 10 Mbps Fiber		10/100 Mbps Copper to 100 Mbps Fiber		10/100/1000 Mbps Copper to 1000 Mbps Fiber	
Distance	Up to 550 m		Up to 80 m		Up to 5 km		Up to 550 m	
Form Factor	Stand-alone / Modular		Stand-alone / Modular		Modular		PCI PC Card	
Dimensions	2.11H x 4.57W x 8.51D cm (0.83H x 1.8W x 3.35D inches)		2.11H x 4.57W x 8.51D cm (0.83H x 1.8W x 3.35D inches)		1.88H x 6.22W x 8.10D cm (0.74H x 2.45W x 3.19D inches)		8.01H x1.84W x 9.53D cm (3.152H x 0.725W x 3.75D inches)	
Power Options	AC Adapter, IE-PowerTray/18 Dual USB Cable		AC Adapter, USB, IE-PowerTray/18 Single USB Cable		Via 1, 4, 8, 12-Slot Chassis		Through PC Workstation Power Supply	
Model/Part# Description	# 856-10730-TX - also requires # 856-10730-RX	TX/SX-MM850-SC	# 855-10622-RX – also requires # 855-10622-RX	MM1300-ST	# 855-12622-TX - also requires # 855-12622-RX	MM1300-ST	# 855-12920-TX - also requires # 855-12920-RX	MM850-SC